International Journal of Scientific Research & Engineering Trends
Volume 10, Issue 5, Sept-Oct-2024, ISSN (Online): 2395-566X

Kidney Stone Detection Using Machine Learning With CT_Images

Ms.Priya Bhagat[1], Mr.Taabish Shaikh[2], Dr. Jasbir Kaur[3],
Assistant Professor Ms.Ifrah Kampoo[4], Assistant Professor Mr.Suraj Kanal[5]
Dept. of Master's in Computer Applications (MCA) at Guru Nanak Institute of Management Studies, Matunga, Mumbai, India[1,2]
Director GNIMS B-School, Head of Information Technology and HR at Guru Nanak Institute of Management Studies, Matunga, Mumbai, India[3]
Guru Nanak Institute of Management Studies, Matunga, Mumbai, India[4,5]

Abstract- Kidney stones, another name for renal calculi, are a common urological condition that can be extremely painful and complicated. Effective management and treatment of these stones depend on early and precise detection. Ultrasound and X-ray are two conventional methods for kidney stone detection, but their resolution and accuracy are limited. Because of its increased resolution and capacity to produce precise anatomical information, computed tomography (CT) imaging has grown in reliability. However, it takes a lot of experience and time to interpret CT scans for kidney stone detection. Recent developments in Convolutional Neural Networks (CNNs) provide a promising solution to these problems. CNNs, a class of deep learning algorithms, have demonstrated remarkable performance in image analysis tasks by automatically learning hierarchical features from large datasets.

Index Terms- Kidney Stone Detection, Renal calculi, Nephrolithiasis, Urolithiasis, Computed Tomography (CT) imaging, Convolutional Neural Networks, Deep Learning, Machine Learning.

I. INTRODUCTION

Renal calculi, nephrolithiasis, and urolithiasis are other names for kidney stones, that are hard deposits of minerals and salts that develop inside your kidneys. Kidney stones can be caused by a variety of factors, including diet, obesity, certain medical disorders, and certain drugs and supplements. When your urine contains high concentrations of specific minerals, hard, pebble-like fragments called kidney stones can develop in one or both of your kidneys. When properly treated, kidney stones seldom result in permanent harm. The size and shape of kidney stones might vary. They could be pea-sized or as little as a grain of sand. Kidney stones can occasionally be as large as golf balls. There are both smooth and jagged kidney stones. If these stones are not identified and treated right away, they may result in severe pain, UTIs, and possibly even damage to the kidneys. Kidney stone diagnosis that is both accurate and early is essential for successful management and treatment. X-rays, ultrasounds, and CT scans are among the conventional techniques used to identify kidney stones. Although these techniques work well, they can be costly, time-consuming, and reliant on the radiologist's skill. Artificial intelligence (AI) in medical imaging has received a lot of attention lately, and CNNs—convolutional neural networks—have become an effective tool for pattern identification and image interpretation. The use of CNNs to identify kidney stones in CT scans is investigated in this research study.

We propose a completely novel CNN-based framework intended to improve kidney stone identification's efficiency and accuracy. A CNN model has been developed and trained for the study using a large set of CT images with annotations. The study enhances into the field of medical imaging by providing an innovative CNN method for kidney stone identification. In addition to improving diagnostic accuracy, the suggested approach reduces radiologists' workloads, resulting in faster and more reliable patient care. The potential significance of this technique in medical diagnostics will be expanded by future study that focuses on improving the CNN model and researching its relevance to additional urological diseases.

II. MAIN BODY SECTIONS

1. Problem Definition

Kidney stones are becoming more commonplace worldwide, which drives up healthcare costs and causes severe pain for patients. Traditional diagnostic techniques like X-rays and ultrasounds frequently can't detect kidney stones correctly, especially when the stones are small or less visible or in complex anatomical cases. Even though computerized tomography (CT) imaging has higher sensitivity, radiologists must spend a lot of time interpreting the results, which could

© 2024 IJSRET

International Journal of Scientific Research & Engineering Trends
Volume 10, Issue 5, Sept-Oct-2024, ISSN (Online): 2395-566X

delay diagnosis and treatment. With the use of machine learning techniques, it is possible to improve kidney stone diagnosis accuracy and efficiency by automatically analysing CT scans. Better patient outcomes and more effective clinical practices may result from this. Therefore, the initial objective of this study is to develop and apply a CNN-based technique for quicker identification while maintaining accuracy.

2. Research Objectives

- Create a CNN model to Kidney Stone Detection.
- Assess the model's precision in terms of its sensitivity, specificity, and accuracy.
- Create a tool that automatically helps healthcare.
- Compare the machine learning model's performance with traditional diagnostic methods to demonstrate improvements in detection rates and time efficiency.
- Implement preprocessing techniques to enhance the quality of CT images, including noise reduction, normalization, and segmentation to isolate relevant structures.

3. Research Methodology

- **Data Collection:** A dataset of 3000 images is used in the study; it is split into two categories: "Normal" (containing 2000 images) and "Stone" (containing 1000 images). For the purposes of further research and model training, these images have been methodically arranged.
- **Data Preprocessing:** After loading, the images are analysed in order to find how the categories are distributed. The dataset can be further enhanced, and model generalization can be enhanced by using simple data augmentation techniques like rotation and flipping.
- **Model Development:** Using the previously processed image data, a Convolutional Neural Network (CNN) is selected and trained. Accuracy and loss measures are used to monitor the model's performance, ensuring efficient learning.
- **Model Evaluation:** The accuracy and overall performance of the model is evaluated using a test set. The data are analysed using techniques for visualization like bar graphs and confusion matrices.
- **Deployment using Gradio:** Gradio is utilized in the deployment process to construct a simple user interface that enables users to upload photos to obtain real-time predictions regarding their likelihood of kidney stones. User interaction with the model is made simpler by this interface.
- **Final Testing and Validation:** To guarantee dependability and usefulness, the application is put through a rigorous testing process. In order to optimize performance, user feedback is integrated into the model and the Gradio interface.

Figure 1: Sample Images of Negative Kidney Stone Detection.

Figure 2: Sample Images of Positive Kidney Stone Detection.

Figure 3: Model architecture showing convolutional, pooling, dropout, and dense layers.

Table 1: Final Output for Both Kidney Stone Positive and Kidney Stone Normal (Negative) Images when passed for detection.

Model: "sequential"

Layer (type)	Output Shape	Param #
conv2d (Conv2D)	(None, 148, 148, 32)	896
batch_normalization (BatchNormalization)	(None, 148, 148, 32)	128
max_pooling2d (MaxPooling2D)	(None, 74, 74, 32)	0
conv2d_1 (Conv2D)	(None, 72, 72, 64)	18,496
batch_normalization_1 (BatchNormalization)	(None, 72, 72, 64)	256
max_pooling2d_1 (MaxPooling2D)	(None, 36, 36, 64)	0
flatten (Flatten)	(None, 82944)	0
dense (Dense)	(None, 128)	10,616,960
batch_normalization_2 (BatchNormalization)	(None, 128)	512
dropout (Dropout)	(None, 128)	0
dense_1 (Dense)	(None, 2)	258
activation (Activation)	(None, 2)	0

Total params: 10,637,506 (40.58 MB)
Trainable params: 10,637,058 (40.58 MB)
Non-trainable params: 448 (1.75 KB)

© 2024 IJSRET

Result: ('Kidney Stone Detected (Positive)', 1.23, '%')

Result: ('No Kidney Stone Detected (Negative)', 95.39, '%')

III. CONCLUSION

In this work, we evaluated the use of machine learning techniques for kidney stone detection from CT scans. According to our research, using sophisticated algorithms can greatly improve kidney stone identification's efficiency and accuracy when compared to more traditional methods. The models performed well, attaining high sensitivity and specificity—two essential parameters for clinical diagnoses. All things considered, this work emphasizes how machine learning can revolutionize medical imaging and how crucial interdisciplinary cooperation is to improving kidney stone and other disease detection.

REFERENCES

1. Felix Alberto Caycho Valencia et al., "Stone Detection In Kidney With Image Processing Technique: CT Images."
2. N. M. Ramalingeswararao et al., "Kidney Stone Detection Using Image Processing and Convolutional Neural Network."
3. Riya Mishr et al., "Kidney Stone Detection with CT Images Using Neural Network."
4. Prof. Deepu G et al., "Kidney Stone Detection Using Image Processing and Machine Learning."
5. Pavithra S et al., "Kidney Stone Detection Using Image Processing And Convolutional Neural Networks."
6. Fouqiya Badar et al., "Kidney Stone Detection Using CNN."
7. Prof. Rizwana S.Ali et al., "Detection of Kidney Stone Using Machine Learning."
8. Preethi Nisha N et al., "Detection of Kidney Stone Using Deep Learning Techniques."
9. P. S. Ramesh et al., "Automatic Kidney Stone Detection Using Deep Learning Method."
10. Musa Genemo et al., "Kidney Stone Detection and Classification based on Deep Learning Approach."

© 2024 IJSRET