

# A Survey of Machine Learning Approaches for High-Quality Image Restoration and Reconstruction

M. Tech Scholar Shubhangi Mansore, Professor Kamlesh Patidar

Department of Computer Science and Engineering  
Jawaharlal Institute of Technology, Borawan Dist. Khargone, MP, India

**Abstract-** The restoration of damaged images has become an essential and highly valuable tool in a wide range of technical applications, including space imaging, medical imaging, and numerous other post-processing techniques. These applications often involve the challenging task of correcting images that have been degraded by factors such as blur and noise. Most image restoration methods begin by simulating the processes that cause image degradation, typically focusing on the effects of blur and noise, and then work to approximate the original image. However, in more realistic real-world scenarios, the challenge is to estimate both the true image and the associated blur based on the characteristics of the degraded image, without relying on any prior knowledge of the blurring mechanism. This situation reflects the complexities encountered when dealing with real-world data. This thesis introduces and develops an innovative approach to digital image restoration, utilizing punctual kriging and various machine learning algorithms. The focus of this research is on restoring images that have been degraded by Gaussian noise, achieving a balance between two competing objectives: maintaining smoothness while preserving edge integrity. This approach aims to enhance the effectiveness of image restoration techniques, particularly in situations where the image has been compromised by environmental and other factors.

**Index Terms-** Image Restoration, Filtering, Noise, Fast Deep Neural Networks, Image Denoising, Augmented Lagrangian Multipliers.

## I. INTRODUCTION

Photos are a good way to share information because they catch rare moments in time and bring the happy memories of many different people into the present. But back then, the only way to keep the few paper pictures people had safe was to put them in picture frames or photo books. Many older pictures' colors have turned yellow because of rust, and they can be damaged if they are handled roughly. Photos that have yellowed or been damaged can now be fixed digitally to look like they did when they were first taken. This makes it possible to keep valuable memories alive for future generations. Deep learning is one of the subfields that make up machine learning as a whole. It is an algorithm for learning from data. Artificial neural networks make up the structure of the program. Deep learning has become more popular in computer vision applications over the last few years because it gives such a good representation of picture data. Several university experts have tried out deep learning on picture projects in order to improve the structure of high-quality material and photo repair methods. Texture skills, especially those of deep convolutional neural networks and generative adversarial networks, are especially good at extracting features, making pictures, and restoring pictures. As a direct

result of this, it is becoming more common to use deep neural networks to rebuild pictures from old photos.

Deep learning is a part of the bigger field of machine learning. Its main goal is to find patterns and regularities in data that are not obvious. When building models for use in deep learning, neural networks are often what are used. The Generative Adversarial Networks (GAN) and the Convolutional Neural Networks (CNN) are two well-known deep learning models. Researchers are coming up with more CNN- and GAN-based image repair models as a way to use these models for picture restoration work. The deep learning-based approach uses very large data sets to make the standard picture repair algorithms better. By teaching it to understand these deep aspects of the picture, you give it the tools to correctly represent the image, which in turn makes the quality of image repair much better.

This article is put together like this. In Section II, there is a summary of what the literature says about how pictures get worse. In Section III, it is described what the problem statement is. In Section IV, we explain what the problem is, why the suggested study is needed, and how important it is. In Section V, we show how to use different types of picture repair in different situations. The end is in Section VI.

## II. LITERATURE WORK

Lastly, the quality assessment index was used to compare the effects of recovering only the salient object vs. restoring only the background in the whole broken picture. It was found that the salient object had a bigger effect on the image quality [12]. This conclusion was made because it was found that restoring only the most noticeable part of a damaged picture worked better than restoring just the background. This was the conclusion that was reached when it became clear that the main focus of the repair effort was the one thing that was being changed back to how it was before.

The generative adversarial network, which is a type of deep neural network, has shown that it can be used to fix a skewed image in the field of image processing. Experiments have shown that the suggested method, which uses cycles of skewed pictures, is a good way to fix photos [13]. The results of the tests showed this to be true.

Photos taken by Sentinel-2 of man-made clouds over two test sites in Italy [14] show that the planned method works. The pictures from the trial were looked at to come up with these findings.

Using this method, cutting-edge performance can be achieved in a variety of uses, such as real-world noise reduction, blind picture super-resolution, and getting rid of JPEG compression artifacts [15].

Because of the repair method that was shown, the contrast of the cryo-TEM pictures is much better, which makes it easier to evaluate the data that was gathered. Also, the authors show that speed can be improved by letting restored picture data do their own processing in the downstream [16]. They do this by showing it on a task called "dense segmentation."

Even though the writers put limits on the methods they used in the experiment they designed together, the results were of a high standard. Even though the processes had some limits, this was still the case. Even so, if the approach described in [17] is used, the speed of such tasks could be improved in terms of how long it takes to do the calculations.

People think that picture completeness and super-resolution are two of the most important parts of picture repair, and they use these two things to judge how well the suggested method works. No matter what kind of picture confusion there is or how bad it is, the results of our tests show that our method is better than the most cutting-edge ways to do these things right now [18].

In-depth, objective reviews and studies of at least five different types of underwater events are needed to prove that these methods can be used in a variety of underwater settings.

At least five different kinds of underwater settings must be used for these reviews and studies. In the end, the writers look at the different problems that can come up during the process of restoring and improving underwater pictures, as well as the questions that still need to be answered. They also make some ideas for areas that could be studied in the future [19]. [Needs citation]

It does this by using the unsharp blurring method on the photo to improve the quality of the picture as a whole. The author used real helicopter shots from around the world to get the pictures that were fixed. This work is checked by using a lot of different overhead photos as input, and the images that are recovered as a result are checked against both aesthetic and quantitative criteria [20].

Extensive study on three of the most common picture background repair problems shows that our DMGN often does a better job than state-of-the-art methods that were made for each task [21]. Some of the things that are being looked into here are how to get rid of picture shadows, image rain streaks, and bring back image dehazing.

When compared to the results of other algorithms that were run on the same set of photos, the results of the suggested method show underwater pictures that look real, have a lot of contrast, and are clear. The author has used both entropy and histogram analysis as measurements for quantitative research in order to prove that the results he or she has gotten are better [22].

Because it has a tiered structure, the JRM-HSR model is both accurate and useful. With the same level of accuracy, JRM-performance HSRs are 16 times faster than JRM-DSR in a single sparse representation and 2 times faster overall [23].

Using a repeated plan based on the Augmented Lagrangian Multipliers (ALM) method is one way to solve the important optimization problem in a time-efficient way. This is just one of many different ways to do things. Experiments with both virtual and real HSI photos [24] show that the quality of the pictures can be greatly improved by using the NHR approach that has been suggested.

The processing performance of the suggested method was good enough, and it was able to improve multiobjective comprehensive processing by reducing background radiation, correcting for spatial variation, and compensating for transfer function [25]. In tests in the lab, the efficiency of diffraction was found to be more than 60%, and the average variation in space was less than 0.2.

In addition, the idea of "authorized aggregation" suggests using a "multi-model approach" to make the network more reliable. With this approach, it's very important to avoid

getting stuck in a situation where the only answer is a local best one. Several tests on deblurring and blocking jobs for grayscale photos show that the suggested method is effective, reliable, and gives repair quality that is on par with the latest technology improvements [26]. The results of these tests show that the algorithm can restore grayscale photos with the same level of quality as the latest technical improvements.

It is strongly suggested that a new and better Subpixel Block Attention (SBA) module be built. This module should recalibrate the blockwise features so that there are fewer blockwise breaks and speed goes up even more. The study shows that these networks offer great trade-offs for removing picture compression artifacts, cleaning up color images, and improving images. rate of writing, number of figures, and how well repairs are done [27].

Table 1: List of Existing Restoration Methods That Have Been Reviewed

S.No.	Method	Advantages	Disadvantages
1	Non Linear Total Variation Restoration Method	Discontinuities much clear than wiener filter method	Creates the staircase effect for images
2	Restoration using Wavelet Analysis	Combined approach produce good results than single approach	Produces artifacts
3	Fourth order PDE Noise Removal Method	Remove blocky effect due more dissipation and improve visual effects	Without gradient parameter higher order PDE produces more dissipation.
4	Hybrid Image Restoration Method	SWT with PSF estimation produces better ISNR	Noise will still exist if Initial estimation of PSF is not well

### III. PROBLEM STATEMENT

The Statement of the Problem The identification of a pixel in an image as belonging to one of the "objects" (i.e., classes) that make up the picture is often done on the basis of some common characteristic(s) or likeness to a chosen set of samples. In other words, the identification of a pixel as belonging to one of the classes that make up the picture is referred to as "classification." This is what people mean when they talk about the "classification" process. This step is done to ensure that the classification is accurate so that further steps may be conducted. In order to determine which aspects of the image may be most accurately categorized as favorable authorll, it is necessary to have some prior knowledge or experience, in addition to making certain educated assumptions about the event.

### IV. PROBLEM FORMULATION/NEED AND SIGNIFICANCE OF PROPOSED RESEARCH WORK

There is now a significant amount of research being conducted on the possible uses of algorithmic approaches to image restoration in a broad number of fields. Present day image restoration may be accomplished using any one of a number of different tried and true methods. Methods such as the Blind image Deconvolution (BID), the Lucy Richardson technique (LRT), the Authoriner filtering process (WFT), and the regularised filtering approach are some examples of these

tactics. There are other more, such as RFT. Every one of these approaches revolves on a certain classification or subcategorization of a filter. In order to make successful use of image restoration algorithms, the most significant challenge that has to be surmounted is to improve the degree to which the quality of the damaged picture can be restored. The objective of the test is to do this. It is essential that the final image that is developed as a result of using a restoration strategy have a high degree of similarity to the usual photograph. This is because the final picture will be shown to the public. It is possible to quantify this resemblance by determining the extent to which the two pictures have the same qualities. The author suggests that the hybrid restoration method should be the key area of focus for the study that is to be done.

### V. RESTORATION OF IMAGES AND ITS USE IN VARIOUS CONTEXTS

The purpose of developing an impression is to bring attention to the most fascinating features of a picture in order to make it more appealing to the viewer, but the purpose of recovering an image is not to give relevant data from a scientific point of view. In other words, developing an impression is not the same thing as restoring an image. To put it another way, the purpose of restoring an image is to highlight the elements of the picture that the viewer will find the most intriguing in order to make the picture more attractive overall. [6] "Imagery programmes" provide impression enhancement tactics that do not rely on the a-priori design of the activity from which the picture was formed. Imagery programmes are also known as "imagery" programmes. These are some of the tactics that may be used to provide a more favorable first impression. Through the use of a strategy called as effigy augmentation, it is possible to effectively cut down on the amount of noise being produced by the problem by surrendering a little amount of the answer. However, not a single one of the numerous software programs that are now available has support for this function. When seen via the lenses of a fluorescence microscope, the uncles'-path possesses a poor resolution. It will be important to create superior methods for visually analyzing photographs in order to extract the item. This will be a need. An application of an IR strategy would be the usage of DE convolution as an example. There is a possibility that the resolution will improve, in particular in the axial direction. There is now noticeably less noise in the background. As a consequence of increasing the amount of the contract, the problem is becoming better. Researchers must spend a significant amount of money to acquire expensive optical equipment such as confocal or two-photon enthusiasm microscopes. As a consequence, there is a need to improve imaging efficiency, which is what encouraged researchers to boost axial resolution using an approach that relies "only" on software. The information that was obtained from the

microscope is solely utilized as supporting evidence for the existence of the object throughout the process of reconstructing the picture. It is not possible to have access to the actual picture itself in any manner. Images obtained using a microscope show a far greater amount of information than what can be seen by the naked eye alone. • Sometimes, the noise that is created as a consequence of other factors obscures or hides the truth. A Users run the risk of having their perceptions distorted by things that are included inside a file viewer. You are able to make deductions, but in order to get to the bottom of things, you will need to employ methods that are not prioritised in the situation.

## VI. CONCLUSION

This article provides a complete examination and analysis of the most contemporary ways for enhancing and preserving underwater photos. The methods covered range from digital image editing to archival storage. In the past, in order to acquire a picture that was clear, one was necessary to take a number of pictures of the same topic while using a number of various pieces of photographic equipment, such as polarizers, sensors, and others. Today, however, one may get a clear image by only taking one shot of the subject using a single piece of equipment. The development of methodologies for computer vision has resulted in the generation of optical models that are capable of generating pictures in areas with low levels of visibility, such as the open air and the depths of the ocean. This has made it possible to explore previously inaccessible locations. The fact that it is difficult for humans to see in these surroundings means that they include areas like these. These models have the ability to take a single image that seems to have been damaged and produce a result that is of a higher quality than the original. As opposed to more conventional methods such as histogram equalization and contrast stretching, the great majority of image enhancement methods start with an optical model of the original, low-quality picture as the foundation for their work. This is in contrast to more conventional methods such as those mentioned before.

## REFERENCES

1. L. Qi et al., "Photoacoustic Tomography Image Restoration With Measured Spatially Variant Point Spread Functions," in *IEEE Transactions on Medical Imaging*, vol. 40, no. 9, pp. 2318-2328, Sept. 2021, doi: 10.1109/TMI.2021.3077022.
2. T. -O. Buchholz, M. Jordan, G. Pigino and F. Jug, "Cryo-CARE: Content-Aware Image Restoration for Cryo-Transmission Electron Microscopy Data," 2019 IEEE 16th International Symposium on Biomedical Imaging (ISBI 2019), 2019, pp. 502-506, doi: 10.1109/ISBI.2019.8759519.
3. R. Mishra, N. Mittal and S. K. Khatri, "Digital Image Restoration using Image Filtering Techniques," 2019 International Conference on Automation, Computational and Technology Management (ICACTM), 2019, pp. 268-272, doi: 10.1109/ICACTM.2019.8776813.
4. Q. He and C. Miao, "Lossless restoration of local blurred image based on deep residual network," 2021 International Conference on Intelligent Transportation, Big Data & Smart City (ICITBS), 2021, pp. 672-676, doi: 10.1109/ICITBS53129.2021.00170.
5. J. Qiu and K. Xie, "A GAN-based Motion Blurred Image Restoration Algorithm," 2019 IEEE 10th International Conference on Software Engineering and Service Science (ICSESS), 2019, pp. 211-215, doi: 10.1109/ICSESS47205.2019.9040717.
6. S. Bao, "An Improved Non-local Mean Filtering Algorithm Based on Medical Image Restoration," 2021 International Conference on Computer Engineering and Artificial Intelligence (ICCEAI), 2021, pp. 43-47, doi: 10.1109/ICCEAI52939.2021.00008.
7. Y. Wang, W. Song, G. Fortino, L. -Z. Qi, W. Zhang and A. Liotta, "An Experimental-Based Review of Image Enhancement and Image Restoration Methods for Underwater Imaging," in *IEEE Access*, vol. 7, pp. 140233-140251, 2019, doi: 10.1109/ACCESS.2019.2932130.
8. K. Panfilova and S. Umnyashkin, "Correlation-based Quality Measure for Blind Deconvolution Restoration of Blurred Images based on Lucy-Richardson Method," 2019 IEEE Conference of Russian Young Researchers in Electrical and Electronic Engineering (EConRus), 2019, pp. 2222-2225, doi: 10.1109/EConRus.2019.8657324.
9. M. Goto and T. Goto, "Performance Improvement of Blind Image Restoration Using Ringing Removal Processing," 2019 IEEE 8th Global Conference on Consumer Electronics (GCCE), 2019, pp. 139-140, doi: 10.1109/GCCE46687.2019.9015431.
10. T. Ueda, K. Yamada and Y. Tanaka, "Underwater Image Synthesis from RGB-D Images and its Application to Deep Underwater Image Restoration," 2019 IEEE International Conference on Image Processing (ICIP), 2019, pp. 2115-2119, doi: 10.1109/ICIP.2019.8803195.
11. J. Lu, F. Yuan, W. Yang and E. Cheng, "An Imaging Information Estimation Network for Underwater Image Color Restoration," in *IEEE Journal of Oceanic Engineering*, vol. 46, no. 4, pp. 1228-1239, Oct. 2021, doi: 10.1109/JOE.2021.3077692.
12. W. Pan, H. Li, Y. Jia, X. Jia and H. Jiang, "Image Restoration and Evaluation Based on Saliency Detection," 2021 IEEE International Conference on Poathorr Electronics, Computer Applications (ICPECA), 2021, pp. 770-772, doi: 10.1109/ICPECA51329.2021.9362586.
13. C. He and Z. Zhang, "Restoration of Underwater Distorted Image Sequence Based on Generative

- Adversarial Network," 2019 IEEE 8th Joint International Information Technology and Artificial Intelligence Conference (ITAIC), 2019, pp. 866-870, doi: 10.1109/ITAIC.2019.8785496.
14. M. Bertoluzza, C. Paris and L. Bruzzone, "A Fast Method for Cloud Removal and Image Restoration on Time Series of Multispectral Images," 2019 10th International Workshop on the Analysis of Multitemporal Remote Sensing Images (MultiTemp), 2019, pp. 1-4, doi: 10.1109/Multi-Temp.2019.8866920.
  15. J. W. Soh and N. I. Cho, "Variational Deep Image Restoration," in IEEE Transactions on Image Processing, vol. 31, pp. 4363-4376, 2022, doi: 10.1109/TIP.2022.3183835.
  16. Singh, Shani Pratap and Shukla, Jayesh and Sharma, Shaili and Daga, khushhal and Bhalavi, Brahman Singh and Singh, Upendra, Face Mask Detection using Multi-Stage CNN Architecture (July 10, 2021). Proceedings of the International Conference on IoT Based Control Networks & Intelligent Systems - ICICNIS 2021, Available at SSRN: <https://ssrn.com/abstract=3884022> or <http://dx.doi.org/10.2139/ssrn.3884022>
  17. A. Saxena, A. Vyas, L. Parashar and U. Singh, "A Glaucoma Detection using Convolutional Neural Network," 2020 International Conference on Electronics and Sustainable Communication Systems (ICESC), Coimbatore, India, 2020, pp. 815-820, doi: 10.1109/ICESC48915.2020.9155930.
  18. B. Bamne, N. Shrivastava, L. Parashar and U. Singh, "Transfer learning-based Object Detection by using Convolutional Neural Networks," 2020 International Conference on Electronics and Sustainable Communication Systems (ICESC), Coimbatore, India, 2020, pp. 328-332, doi: 10.1109/ICESC48915.2020.9156060.
  19. Gupta, P., Shukla, M., Arya, N., Singh, U., Mishra, K. (2022). Let the Blind See: An AIoT-Based Device for Real-Time Object Recognition with the Voice Conversion. In: Al-Turjman, F., Nayyar, A. (eds) Machine Learning for Critical Internet of Medical Things. Springer, Cham. [https://doi.org/10.1007/978-3-030-80928-7\\_8](https://doi.org/10.1007/978-3-030-80928-7_8)
  20. Patidar, M., Singh, U., Shukla, S.K. et al. An ultra-area-efficient ALU design in QCA technology using synchronized clock zone scheme. J Supercomput (2022). <https://doi.org/10.1007/s11227-022-05012-2>
  21. X. Feng, W. Pei, Z. Jia, F. Chen, D. Zhang and G. Lu, "Deep-Masking Generative Network: A Unified Framework for Background Restoration From Superimposed Images," in IEEE Transactions on Image Processing, vol. 30, pp. 4867-4882, 2021, doi: 10.1109/TIP.2021.3076589.
  22. G. Sequeira, V. Mekkalki, J. Prabhu, S. Borkar and M. Desai, "Hybrid Approach for Underwater Image Restoration and Enhancement," 2021 International Conference on Emerging Smart Computing and Informatics (ESCI), 2021, pp. 427-432, doi: 10.1109/ESCI50559.2021.9397058.
  23. W. Li, N. Sang, C. Gao and Y. Shao, "Joint Image Restoration and Matching Based on Hierarchical Sparse Representation," 2019 IEEE International Conference on Image Processing (ICIP), 2019, pp. 4494-4498, doi: 10.1109/ICIP.2019.8803466.
  24. Y. Hu and X. Li, "Hyperspectral Image Restoration using Nonconvex Hybrid Regularization," IGARSS 2019 - 2019 IEEE International Geoscience and Remote Sensing Symposium, 2019, pp. 393-396, doi: 10.1109/IGARSS.2019.8900162.
  25. S. Jiang, X. Zhi, W. Zhang, D. Wang, J. Hu and C. Tian, "Global Information Transmission Model-Based Multiobjective Image Inversion Restoration Method for Space Diffractive Membrane Imaging Systems," in IEEE Transactions on Geoscience and Remote Sensing, vol. 60, pp. 1-12, 2022, Art no. 5607612, doi: 10.1109/TGRS.2021.3083111.
  26. S. Li, B. Qin, J. Xiao, Q. Liu, Y. Wang and D. Liang, "Multi-Channel and Multi-Model-Based Autoencoding Prior for Grayscale Image Restoration," in IEEE Transactions on Image Processing, vol. 29, pp. 142-156, 2020, doi: 10.1109/TIP.2019.2931240.
  27. T. Kim, C. Shin, S. Lee and S. Lee, "Block-Attentive Subpixel Prediction Networks for Computationally Efficient Image Restoration," in IEEE Access, vol. 9, pp. 90881-90895, 2021, doi: 10.1109/ACCESS.2021.3091975.
  28. A. Taiwade, N. Gupta, R. Tiwari, S. Kumar and U. Singh, "Hierarchical K-Means Clustering Method for Friend Recommendation System," 2022 International Conference on Inventive Computation Technologies (ICICT), 2022, pp. 89-95, doi: 10.1109/ICICT54344.2022.9850852.
  29. R. Baghel, P. Pahadiya and U. Singh, "Human Face Mask Identification using Deep Learning with OpenCV Techniques," 2022 7th International Conference on Communication and Electronics Systems (ICCES), 2022, pp. 1051-1057, doi: 10.1109/ICCES54183.2022.9835884.
  30. M. Ranjan, A. Shukla, K. Soni, S. Varma, M. Kuliha and U. Singh, "Cancer Prediction Using Random Forest and Deep Learning Techniques," 2022 IEEE 11th International Conference on Communication Systems and Network Technologies (CSNT), 2022, pp. 227-231, doi: 10.1109/CSNT54456.2022.9787608.
  31. Singh, Upendra, Gupta, Puja, and Shukla, Mukul. 'Activity Detection and Counting People Using Mask-RCNN with Bidirectional ConvLSTM'. 1 Jan. 2022 : 6505 – 6520.
  32. Gupta, P., Shukla, M., Arya, N., Singh, U., Mishra, K. (2022). Let the Blind See: An AIoT-Based Device for Real-Time Object Recognition with the Voice Conversion. In: Al-Turjman, F., Nayyar, A. (eds) Machine

Learning for Critical Internet of Medical Things.  
Springer, Cham. [https://doi.org/10.1007/978-3-030-80928-7\\_8](https://doi.org/10.1007/978-3-030-80928-7_8)

33. Patidar, M., Singh, U., Shukla, S.K. et al. An ultra-area-efficient ALU design in QCA technology using synchronized clock zone scheme. *J Supercomput* (2022). <https://doi.org/10.1007/s11227-022-05012-2>