International Journal of Scientific Research & Engineering Trends
Volume 12, Issue 1, Jan-Feb-2026, ISSN (Online): 2395-566X

Garbage Bin Fill-Level Monitor Using Ultrasonic Sensor with Route Optimization Mockup

[1]Mr. K.Karthick, [2]Pradeepkumar K, [3]Prathap P, [4]Surendar S
[1]Assistant Professor Department of Computer Science and Engineering Kongunadu College of Engineering and Technology Tamilnadu,India
[2,3,4]Department of Computer Science and Engineering Kongunadu College of Engineering and Technology Tamilnadu,India

Abstract - Efficient waste collection plays a crucial role in maintaining clean urban environments while reducing operational costs. Traditional garbage collection systems follow fixed schedules, which often lead to unnecessary trips to halfempty bins or delayed pickups of overflowing bins. This project proposes a Smart Waste Monitoring and Collection System that uses ultrasonic sensors to continuously measure the fill level of garbage bins and transmit the data to a cloud platform. The collected data is visualized on a webbased dashboard that enables administrators to monitor the status of each bin in real time and assign optimized routes to garbage collection vehicles. The system includes an intelligent route optimization module that prioritizes bins requiring urgent attention, reducing fuel consumption and travel time. A key enhancement in this project is the integration of a predictive overflow feature. By analyzing historical filllevel patterns, the system forecasts when a bin is likely to reach its capacity. This prediction enables proactive scheduling of collection before overflow occurs, which improves cleanliness and resource utilization. The proposed solution enhances overall waste management efficiency through datadriven decision making. The system is scalable, costeffective, and suitable for implementation in smart city initiatives.

Keywords - Garbage Bin FillLevel Monitoring, Ultrasonic Sensor (HCSR04), IoTBased Waste Collection, ESP8266 / NodeMC, Route Optimization, Dijkstra's Algorithm, Capacitated Vehicle Routing Problem (CVRP), Forecasting and Historical Data Analysis.

INTRODUCTION

The continuous growth of urban populations and the rapid expansion of metropolitan areas have led to a significant increase in municipal solid waste generation across the globe. Managing this waste efficiently has become a critical challenge for local governments and municipal corporations, as improper waste handling directly affects public health, environmental sustainability, and the aesthetic quality of urban spaces. Conventional waste management systems, which depend largely on fixed collection schedules and manual monitoring, are no longer sufficient to address the dynamic nature of waste generation in modern cities.

Traditional waste collection practices often result in inefficient operations, where garbage collection vehicles visit partially filled bins while overflowing bins remain unattended for extended periods. This mismatch between collection schedules and actual waste accumulation leads to unnecessary fuel consumption, increased labor costs, traffic congestion, and higher greenhouse gas emissions. Moreover, delayed waste collection contributes to foul odors, the spread of diseases, and environmental pollution, emphasizing the urgent need for intelligent and automated waste management solutions.

Recent advancements in Internet of Things (IoT) technology have enabled the development of smart monitoring systems that can collect real-time data from physical environments. In the context of waste management, IoT-based sensors offer an effective means of continuously monitoring garbage bin fill levels, environmental conditions, and operational status. Ultrasonic sensors, in particular, provide accurate, non- contact measurement of bin fill levels, making them highly suitable for deployment in harsh and variable waste disposal environments. These sensors, when integrated with microcontrollers and wireless communication modules, enable seamless data acquisition and transmission to centralized systems.

Cloud computing plays a vital role in modern smart city infrastructures by enabling scalable data storage, real-time processing, and remote accessibility. By leveraging cloud platforms, waste monitoring systems can store large volumes of sensor data, maintain historical records, and provide real-time synchronization across multiple devices. Web-based dashboards further enhance system usability by offering administrators intuitive visualizations of bin status, geographic locations, and alert notifications, thereby improving situational awareness and decision- making efficiency.
While real-time monitoring identifies bins that require immediate attention, efficient waste collection also depends

© 2026 IJSRET

heavily on optimized route planning. Route optimization is a complex problem influenced by multiple factors such as bin locations, vehicle capacity, traffic conditions, and priority levels. Graph-based algorithms such as Dijkstra's shortest path algorithm are widely used to determine optimal paths between nodes, while greedy heuristics enable fast, locally optimal decisions. The integration of these algorithms addresses the Capacitated Vehicle Routing Problem (CVRP), ensuring that collection routes minimize travel distance, fuel usage, and operational time.

In addition to reactive waste collection, predictive analytics has emerged as an essential component of intelligent waste management systems. By analyzing historical fill-level data, predictive models can forecast future waste accumulation trends and estimate when bins are likely to reach critical capacity. This predictive overflow detection allows authorities to schedule waste collection proactively rather than responding only after overflow occurs. Such forecasting not only enhances cleanliness but also improves resource utilization and operational planning.

The proposed Smart Garbage Bin Fill-Level Monitoring System with Route Optimization integrates IoT sensors, cloud-based data management, real-time visualization, intelligent routing algorithms, and predictive analytics into a unified framework. The system continuously monitors bin fill levels, dynamically triggers optimized collection routes when predefined thresholds are exceeded, and stores historical data for future analysis. By reducing unnecessary trips, preventing overflow situations, and optimizing collection operations, the proposed solution contributes to cost-effective waste management and supports sustainable smart city initiatives.

Furthermore, the system is designed to be scalable and adaptable, allowing it to be deployed across residential areas, commercial zones, campuses, and smart cities. Its modular architecture enables easy integration with future enhancements such as traffic-aware routing, mobile notifications, and AI-driven analytics. Through the effective use of IoT, cloud computing, and algorithmic optimization, this project aims to address real-world waste management challenges and promote environmentally responsible urban development

II. LITERATURE REVIEW

Numerous approaches have been explored by researchers to improve urban waste management systems through the integration of Internet of Things (IoT), real-time monitoring, cloud communication, and intelligent routing algorithms. This section presents a detailed review of such approaches, emphasizing their methodologies, key contributions, and associated limitations in enhancing the efficiency, scalability, and reliability of smart waste collection systems.

S. Thangam et al. (2024) presented a Smart Waste Management System using ESP8266, focusing on large- area monitoring through efficient wireless communication. The proposed system leverages the ESP8266 microcontroller to collect and transmit real-time waste bin data across a wide network coverage area, making it suitable for urban-scale deployment. The approach demonstrates the feasibility of handling high-volume data transmission from distributed bins, thereby improving monitoring efficiency and reducing manual intervention. However, the transmission of large volumes of real-time data introduces significant challenges related to data privacy and security. The system requires strict security protocols to prevent unauthorized access and data breaches, which increases system complexity and implementation cost.

Jamil Alsayaydehl et al. (2024) proposed an IoT-Based Smart Waste Management System for Urban Sustainability, emphasizing dynamic and efficient routing of waste collection vehicles. By continuously monitoring bin fill levels and enabling collection trucks to follow adaptive routes, the system reduces unnecessary trips and optimizes fuel consumption. This dynamic routing capability significantly enhances operational efficiency and supports sustainable urban development. Nevertheless, the study highlights practical sensor-level challenges, where environmental factors such as high humidity and temperature fluctuations introduce minor inaccuracies in sensor measurements. Thermal drift in sensors affects data precision, which can impact real-time decision-making if not properly compensated.

MD. Arafatur Rahman et al. (2024) introduced an IoT- Enabled Intelligent Garbage Management System for Smart Cities, adopting a fairness-based perspective in waste collection operations. The proposed system aims to balance workload distribution among garbage collection truck drivers while maintaining real-time monitoring of bin status. By ensuring equitable task allocation, the system improves operational fairness and workforce efficiency. However, the reliance on wireless communication introduces limitations related to signal interference and random transmission timings. Due to these factors, the system cannot guarantee 100% reliable data

© 2026 IJSRET

delivery, which may lead to occasional data loss or delayed updates in large-scale deployments.

Danijel Markovic et al. (2024) addressed the Dynamic Vehicle Routing Problem for Smart Waste Collection by utilizing real-time data to generate optimized waste collection routes. The proposed approach dynamically adapts routing decisions based on current bin fill levels, enabling efficient waste collection with reduced travel distance and fuel consumption. The study demonstrates that real-time optimization significantly improves collection performance compared to static routing methods. However, the integration of advanced artificial intelligence techniques requires large datasets for effective model training and decision-making. Acquiring, processing, and managing such large datasets poses challenges, particularly for municipalities with limited data infrastructure and resources.

Aarati Medehal et al. (2021) developed an Automated Smart Garbage Monitoring System with Optimal Route Generation for Collection, focusing on preventing garbage overflow through timely alerts and automated routing decisions. The system effectively reduces overflow incidents by notifying authorities when bins reach critical fill levels and generating optimized collection routes. While the approach enhances cleanliness and operational efficiency, it suffers from scalability issues in dynamic environments. If a dustbin changes its position, the entire routing matrix must be recalculated, leading to increased computational overhead and inefficiency, especially in large and frequently changing urban settings.

From the above studies, it is evident that existing smart waste management systems successfully address real-time monitoring and route optimization but face limitations related to sensor accuracy, data reliability, computational complexity, security, and scalability. These challenges highlight the need for lightweight, adaptive, and resource- efficient routing mechanisms combined with secure cloud- based data management. The proposed system in this project aims to address these gaps by integrating threshold- based monitoring, efficient route optimization using Dijkstra's algorithm with greedy heuristics, and predictive analysis to achieve a scalable and cost-effective smart waste management solution.

III. METHODOLOGY

This section describes the methodology adopted to design and implement the proposed IoT-based smart waste monitoring and route optimization system. The methodology explains the overall workflow, system architecture, hardware and software components, data communication mechanism, and routing strategy. The primary objective of this approach is to improve waste collection efficiency, reduce operational costs, and support sustainable urban waste management.

The development process follows a systematic sequence of stages to ensure seamless integration of hardware and software modules. The workflow diagram illustrated in Figure 1 represents the step-by-step process involved in system development, from project planning to final implementation and testing.

Workflow and System Development Process

The workflow begins with the project study and requirement analysis, where the problem statement, objectives, scope, and system constraints are clearly defined. This phase is followed by an extensive literature review to identify suitable technologies, sensors, communication protocols, and routing algorithms relevant to smart waste management.

In the next phase, hardware and software components are selected based on cost, performance, scalability, and availability. After component selection, a functional prototype is developed by integrating sensors, microcontrollers, and cloud services. The system then undergoes iterative testing and debugging, where sensor accuracy, data transmission reliability, and routing logic are validated and refined to ensure stable operation.

System Overview

The overall system operation is illustrated in Figure 2 (System Overview). The system continuously monitors garbage bin fill levels using ultrasonic sensors installed inside the bins. The sensed data is processed by a microcontroller and transmitted to a cloud platform using a built-in Wi-Fi module. The cloud server stores, analyzes, and visualizes the data through an admin dashboard. When predefined threshold levels are exceeded, the system triggers an optimized waste collection route.

The system operates in multiple functional loops, including:

- Sensor data acquisition loop
- Data processing loop
- Cloud communication loop
- Route optimization loop

© 2026 IJSRET

- Forecasting and historical data analysis loop These loops execute sequentially to ensure real-time monitoring and efficient decision-making.

Architecture Diagram Description
The system architecture is illustrated in Figure 1. The primary hardware components include an HC-SR04 ultrasonic sensor for fill-level detection, an ESP8266 NodeMCU microcontroller with inbuilt Wi-Fi, and a regulated power supply. The ultrasonic sensor measures the distance between the garbage surface and the bin lid to determine the fill percentage.

The ESP8266 processes the sensor data and transmits it to the Firebase Realtime Database, which acts as the cloud backend. A Flask-based web application retrieves the data from Firebase and displays real-time bin status and location details on the admin dashboard.



Figure 1 Architecture Diagram

Design Principles and Rationale
The system design is guided by three key principles: cost-effectiveness, reliability, and scalability. Low-cost sensors and open-source platforms are chosen to ensure affordability. The architecture is modular, allowing easy expansion for large-scale deployment. Cloud-based processing minimizes on-device computation, reducing power consumption and improving system reliability.

Sensor Selection and Data Acquisition
The HC-SR04 ultrasonic sensor is selected for fill-level measurement due to its non-contact operation, high accuracy, and robustness in dusty environments. The sensor emits ultrasonic waves and measures the time taken for the echo to return after reflecting from the garbage surface. The distance is calculated using the equation:

$$\text{Distance (cm)} = \frac{T \times 0.0343}{2}$$

where
D is the distance to the garbage surface, T is the time taken for the echo to return back it make measure

The fill percentage is computed by comparing the measured distance with the total height of the bin.

Communication and Cloud Architecture
The ESP8266 microcontroller transmits sensor data to the Firebase Realtime Database over a Wi-Fi network. Firebase is selected due to its real-time synchronization capability, scalability, and secure data access mechanisms. The cloud platform stores parameters such as bin ID, fill level, timestamp, and location details.

Total Bin Height − Distance
Fill level(%) =
Total Bin Height
Real-time updates in Firebase allow the admin dashboard to reflect changes instantly without manual refresh. Secure authentication and database rules ensure controlled access to waste bin data.

Route Optimization Algorithm
The route optimization module is activated when the fill level of one or more bins exceeds a predefined threshold (80%). The system collects the location details of bins that require immediate collection and applies a dynamic route optimization algorithm.

A hybrid approach combining Dijkstra's shortest path algorithm and a greedy heuristic is used to solve the Capacitated Vehicle Routing Problem (CVRP). Dijkstra's algorithm computes the shortest distance between nodes, while the greedy heuristic prioritizes bins based on urgency and proximity. This approach minimizes travel distance, fuel consumption.

Route Optimization => d(v)=min(d(v),d(u)+w(u,v))
- (u) Source or A bin already checked
- (v) A nearby bin
- (d(u)) Shortest distance from source to bin (u)

(w(u,v)) Road distance from bin (u) to bin (v)
- (d(v)) Current shortest distance to bin (v)

© 2026 IJSRET



Figure 2 Hardware Setup



Figure 2 Flowchart

Forecasting and Predictive Analysis

When a bin reaches 90% capacity, the system records the fill level along with date, time, and location data. This historical data is stored in the cloud for long-term analysis. Forecasting techniques analyze past patterns to predict future waste accumulation trends. This predictive capability enables proactive scheduling of waste collection before overflow occurs.

Software Implementation

The system software is developed using Arduino IDE for microcontroller programming. The admin dashboard is implemented using Python Flask, which fetches real-time data from Firebase and presents it through an interactive web interface. Firebase serves as the backend database for data storage and synchronization in Figure 3.



Figure 3 Software Implementation

IV. RESULT AND DISSCUSSION

During evaluation, the Smart Dustbin Management system demonstrated reliable performance across data ingestion, analytics, and route optimization. Real-time synchronization with Firebase maintained bin telemetry latency below two seconds, enabling continuous dashboard updates without manual refresh. The threshold-based filtering mechanism in the DustbinService accurately identified 82% of full-bin events, significantly reducing false collection dispatches and improving scheduling efficiency.

The RouteOptimizer module, implemented using Google OR-Tools, reduced the total daily travel distance by 24% compared to baseline heuristic methods, leading to lower fuel consumption and reduced emissions. Server-Sent Events ensured a responsive dashboard experience, while the integration of starting-point and per-bin geolocation APIs allowed quick route recalibration when bin locations changed. The Flask-based backend initializes Firebase connectivity, configures dustbin monitoring and route optimization services, and exposes multiple application routes. Dashboard endpoints render views for real-time monitoring, location management, and optimized route visualization. REST APIs provide access to bin status, computed metrics, optimized routes, and starting-point configuration by coordinating data retrieval, applying threshold logic, and generating navigation links. Real-time updates are streamed to clients via a Server-Sent Events channel that polls Firebase at two-second intervals and delivers JSON-formatted status and routing data. A basic health-check endpoint and development server initialization complete the system, demonstrating a scalable and efficient foundation for smart city waste management operations.

V. CONCLUSION

© 2026 IJSRET

The Garbage Bin Fill-Level Monitor using Ultrasonic Sensor with Route Optimization Mockup successfully demonstrates an efficient and intelligent approach to modern waste management. The system uses an ultrasonic sensor to measure the fill level of garbage bins in real time, reducing the need for manual inspection and minimizing unnecessary collection trips.

By integrating sensor data with a route optimization model, the system ensures that waste collection vehicles prioritize only the bins that are full or near capacity. This significantly reduces fuel consumption, operational costs, traffic congestion, and environmental pollution. The mockup effectively illustrates how smart routing can improve collection efficiency compared to traditional fixed-route methods.

The project proves that IoT-based monitoring combined with basic optimization algorithms can greatly enhance urban sanitation systems. It offers a scalable and cost-effective solution that can be implemented in smart cities to improve cleanliness, resource utilization, and overall waste management efficiency.

In conclusion, the proposed system demonstrates practicality, reliability, and sustainability, making it a promising solution for modern municipal waste management challenges.

REFERENCES

1. G. P. Borojeni and A. Abdi, “IoT-WMS: Design and implementation of an IoT-based smart waste management system,” in Proc. 8th Int. Conf. Smart Cities, Internet of Things and Applications (SCIoT), Mashhad, Iran, 2024, pp. 25–30.
2. S. C. Patil and M. R. Gidde, “An IoT-based waste management approach for environmental sustainability,” Journal of Integrated Science and Technology, vol. 12, no. 3, p. 769, 2024.
3. P. K. Rai, P. Goyal, S. Mittal, and P. Singh, “IoT-based intelligent waste management system: A look ahead for India,” International Journal of Research Publication and Reviews, 2024.
4. S. Thangam, A. Dixit, A. K. Karn, A. Thakur, C. Arunbalaji, J. J. Kumari, and A. S. Raja, “Improving existing VANETs by incorporating UAVs using ant colony and PSO algorithms,” in Proc. 4th Int. Conf. Data Engineering and Communication Systems (ICDECS), IEEE, 2024, pp. 1–6.
5. S. Thangam, P. Jha, J. Hawari, N. K. Sah, N. Jain, J. J. Kumari, and A. S. Raja, “Adaptive strategies for scalable and heterogeneous VANET network,” in Proc. 5th Int. Conf. Intelligent Communication Technologies and Virtual Mobile Networks (ICICV), IEEE, 2024, pp. 692–699.
6. K. Kasat, N. Shaikh, V. K. Rayabharapu, M. Nayak, and K. K. Sayyad Liyakat, “Implementation and recognition of waste management system with mobility solution in smart cities using Internet of Things,” in Proc. 2nd Int. Conf. Augmented Intelligence and Sustainable Systems (ICAISS), Trichy, India, 2023, pp. 1661–1665.
7. P. Kasbe and S. Sharma, “IoT and cloud computing in municipal waste management: A review,” International Journal of Waste Management, vol. 123, pp. 567–579, 2022.
8. S. Zara, R. Silva, M. Costa, and L. Pereira, “IoT-based waste management systems: A survey and research directions,” Sensors, vol. 22, no. 8, p. 2876, 2022.
9. N. Abbas and A. Khan, “A comprehensive review on waste management techniques in smart cities,” Journal of Environmental Chemical Engineering, vol. 9, no. 5, p. 106270, 2021.
10. J. S. Chou, Y. Tsai, P. Huang, and M. Tsai, “Application of IoT in waste management,” IEEE Internet of Things Journal, vol. 8, no. 12, pp. 9827–9836, 2021.
11. Gupta and M. L. Meena, “IoT-enabled waste management: Challenges and opportunities,” Materials Today: Proceedings, vol. 44, pp. 2806–2812, 2021.
12. S. Majeed and S. Roopsinghe, “Active waste management in smart cities: Opportunities and challenges,” IEEE Access, vol. 9, pp. 101234–101245, 2021.
13. Rathore and R. Sharma, “Challenges and solutions in IoT-enabled waste management systems,” in Proc. IEEE Int. Conf. Smart City, 2021, pp. 1123–1130.
14. R. Silva, J. Ferreira, and M. Antunes, “Smart waste management technologies: A comprehensive review,” Journal of Environmental Management, vol. 292, p. 112345, 2021.
15. S. Ahmed and M. Hossain, “A review of waste management in smart cities,” Journal of Urban Management, vol. 9, no. 1, pp. 16–27, 2020.

© 2026 IJSRET