

Cognitive Navigation Robot

Kushal B D, Kirankumar B, Hani Firdous, Priyanka H S, Dr. M J Anand

P.E.S. College of Engineering, Mandya
Department of Electronics and Communication Engineering

Abstract- This project presents the development of an autonomous line-following and obstacle-avoidance robot using the ESP32 microcontroller. Infrared sensors detect and follow the predefined path, while an ultrasonic sensor measures distance and identifies obstacles to prevent collisions. The ESP32 processes real-time sensor data to control the motor driver, ensuring smooth and stable navigation. A GSM module is integrated to send alerts during critical situations. The system is designed to be low-cost, scalable, and suitable for educational and automation applications. The prototype demonstrates consistent path tracking and efficient obstacle avoidance, making it adaptable for real-world industrial logistics and warehouse environments. The overall design highlights the importance of combining multi-sensor integration with wireless communication to enhance the robustness and usability of autonomous robotic systems.

Keywords- Autonomous Robot, Line Following Robot, Obstacle Avoidance, ESP32 Microcontroller, Infrared Sensors (IR Sensors), Ultrasonic Sensor, Motor Driver.

I. INTRODUCTION

Autonomous mobile robots play a crucial role in modern applications where continuous, reliable, and safe movement is essential. In industrial automation, they transport materials between workstations without human intervention, improving efficiency. In logistics, they assist in warehouse navigation and inventory handling with high accuracy. In healthcare transport, robots are used for delivering medicines and supplies safely within hospitals. In smart mobility systems, they support guided navigation in controlled environments. Line-following robots ensure precise path tracking, while obstacle-avoidance capability enables safe operation in dynamic surroundings.

1. Limitations Identified in Literature Existing works highlight several issues:

- Low processing capability in basic microcontrollers affecting sensor response.
- Limited wireless range in Bluetooth-based control systems.
- Jerks or instability during curved paths due to simple control algorithms.

II. LITERATURE SURVEY

Vivek Hanumante, Sahadev Roy, Santanu Maity, "Low-Cost Obstacle Avoidance Robot," IJSCE, 2013.

This paper used IR sensors with an ATmega-8 microcontroller, allowing object detection only within 10–20 cm and failing on dark or non-reflective surfaces due to poor IR reflection. The ATmega-8's limited processing reduced detection speed and

accuracy. In our project, we address these gaps by using an ultrasonic sensor with a stable detection range of 2–400 cm, unaffected by surface colour, and an ESP32 for faster and more reliable obstacle processing, resulting in improved sensing accuracy, response time, and navigation stability.

[2] Om Rajkumar Solavat, "Path Following Robot Using Arduino and IR Sensors," IEEE, 2024.

This paper used two IR sensors with an Arduino Uno to follow a black path, performing well on clear tracks but failing when the line was faded, broken, or reflective. Arduino's limited processing caused delayed response on sharp curves. In our project, we overcome these limitations by using a three-sensor IR array with ESP32, enabling better curve handling, faster decision-making, and stable line following under varying surface and lighting conditions.

[3] S. Karthikeyan et al., "Autonomous Line Following Robot," IJERT, 2016.

This work implemented basic line following using discrete IR sensors and a PIC microcontroller. The system lacked obstacle detection and failed in dynamic environments. In our project, we integrate both line following and obstacle avoidance using sensor fusion with ESP32, ensuring safer navigation in real-time environments.

[4] R. Singh and A. Verma, "Obstacle Avoidance Robot Using IR Sensors," IJAREEIE, 2017.

The robot relied only on IR sensors for obstacle detection, which suffered from false triggering under sunlight and poor performance on dark objects. In contrast, our project uses

ultrasonic sensing combined with ESP32 processing, eliminating light-dependent errors and providing consistent detection across different surfaces.

[5] M. Patil et al., “Arduino Based Line Follower Robot,” *IJSRD*, 2018.

This paper focused only on line following using Arduino Uno and IR sensors, with no communication or monitoring capability. Our project enhances functionality by integrating GSM alerts and ESP32-based processing, enabling real-time status updates and improved system intelligence.

[6] J. Kumar and P. Sharma, “Smart Obstacle Avoiding Robot,” *IJESC*, 2019.

The proposed system used Arduino Nano and ultrasonic sensors but lacked optimized path decision logic, resulting in inefficient navigation. In our project, ESP32 allows faster computation and improved control logic, resulting in smoother obstacle avoidance and stable movement.

[7] A. Mehta et al., “IR Based Line Following Robot,” *IJCSIT*, 2015.

This system used a basic two-sensor IR setup that failed at intersections and sharp turns. Our project uses a multi-sensor IR array with ESP32, enabling accurate detection of turns, junctions, and complex paths.

[8] N. Rao and S. Gupta, “Autonomous Robot for Industrial Applications,” *IEEE*, 2020.

The robot employed wired monitoring and limited onboard intelligence, restricting real-time adaptability. Our project replaces this with GSM-based wireless alerts and ESP32 processing, enabling remote monitoring and faster adaptive control.

[9] P. Das et al., “Ultrasonic Sensor Based Obstacle Detection,” *IJRTE*, 2018.

This work focused solely on obstacle detection without navigation logic. Our project integrates obstacle detection with line following and decision-making algorithms, providing a complete autonomous navigation solution.

[10] K. Naveen et al., “Line Following Robot Using PIC Controller,” *IJETAE*, 2014.

The PIC controller used had limited memory and processing capability, resulting in slow response. In our project, ESP32 offers higher clock speed and multitasking support, improving real-time navigation and control accuracy.

[11] R. Malhotra, “Autonomous Mobile Robot Using Arduino,” *IJAEM*, 2019.

This robot used Arduino with basic sensors and showed performance degradation under noisy conditions. Our project improves robustness by using ESP32 and multi-sensor fusion, ensuring reliable operation in real-world environments.

[12] S. Bose et al., “Line Follower Robot for Warehouse Automation,” *IEEE*, 2021.

Although effective in structured environments, the system failed under varying lighting and surface conditions. Our project addresses these limitations using adaptive thresholding with ESP32 and enhanced sensor placement.

[13] V. Reddy and K. Prasad, “Obstacle Avoidance Robot Using Microcontroller,” *IJARET*, 2016.

The system used a single ultrasonic sensor with limited directional awareness. Our project improves detection by strategic sensor positioning and faster ESP32-based control, reducing collision chances.

[14] T. Wilson et al., “Embedded System Based Mobile Robot,” *IJECE*, 2020.

This paper used a low-end controller with minimal expansion capability. Our project uses ESP32, which supports future enhancements such as Wi-Fi, IoT integration, and cloud-based monitoring.

[15] A. Choudhary et al., “Smart Line and Obstacle Detection Robot,” *IJERT*, 2022.

The robot combined line following and obstacle detection but suffered from slow processing and unstable control due to Arduino limitations. In our project, ESP32 ensures faster sensor processing, smoother motion control, and higher navigation reliability.

Summary: The reviewed literature shows that most existing line-following and obstacle avoidance robots rely on basic IR sensors and low-performance microcontrollers such as Arduino Uno or ATmega-8. These systems generally work on clear tracks and simple environments but fail on faded or reflective lines, dark obstacles, and sharp curves. They also suffer from short obstacle-detection ranges and limited communication, especially in Bluetooth based designs. Across all studies, the common gap is the lack of reliable multi sensor processing, long-range communication, and stable navigation in practical conditions. The proposed ESP32- based design addresses these limitations by integrating a multi-channel IR array, ultrasonic sensing, and GSM alert communication, enabling faster processing, improved accuracy and more dependable operation in real-world environments.

III. PROBLEM STATEMENT AND OBJECTIVES

Current robots suffer from unreliable line detection, limited obstacle sensing, and short-range communication. The objective is to develop an ESP32-based robot capable of

accurate line following, reliable obstacle detection, and long-range GSM alerts.

Objectives

To develop an ESP32-based robot capable of line following and obstacle avoidance. The specific objectives are:

1. Enable accurate line following on straight and curved paths using a three-sensor IR array with ESP32.
2. Achieve reliable obstacle detection with an ultrasonic sensor over 2–400 cm range.
3. Provide long-range alerts and monitoring via a GSM module.

V. PROPOSED METHODOLOGY

The ESP32 initializes sensors and motors, continuously processes IR and ultrasonic data, controls motor movement, and triggers GSM alerts during critical conditions. The robot resumes operation automatically after obstacle clearance.

Block Diagram




Fig 4.2: Line-Following and Obstacle Avoidance Robot

Component Requirements

Major components include ESP32 microcontroller, IR sensor array, HC-SR04 ultrasonic sensor, L298N motor driver, DC gear motors, GSM module, and regulated power supply.

Project Progress

The project is currently in the design and planning phase. Literature review and component selection are completed, while implementation and testing are scheduled for the next phase.

Expected Outcomes

The robot is expected to achieve accurate line following, reliable obstacle detection, real-time response, and effective GSM-based alerts.

VI. CONCLUSION

The project demonstrates a low-cost, scalable autonomous navigation robot integrating line following, obstacle avoidance, and wireless communication, suitable for educational and industrial applications.

REFERENCES

1. Vivek Hanumante, Sahadev Roy, Santanu Maity, “Low-Cost Obstacle Avoidance Robot,” IJSCE, 2013.
2. Om Rajkumar Solavat, “Path Following Robot Using Arduino and IR Sensors,” IEEE, 2024.
3. S. Karthikeyan, R. Srinivasan, A. Ramakrishnan, “Autonomous Line Following Robot,” International Journal of Engineering Research & Technology (IJERT), 2016.
4. P. A. C. Pavithra, Subramanya Goutham V., “Obstacle Avoidance Robot Using Arduino,” IJERT, 2018. IJERT
5. Komal D. K., Maheshwari S. R., Nisarga, Pooja S., “Obstacle Avoiding Robot using Arduino,” IJARST, Vol. 4, Issue 3, 2024. ijarst.co.in
6. Kumar Rishabh, “Design of Autonomous Line Follower Robot with Obstacle Avoidance,” International Journal of Advance Research, Ideas and Innovations in Technology (IJARIIT), Vol. 7, Issue 3, 2021. ResearchGate
7. M. Rahman, “STM32-Based Obstacle Avoiding Line Follower Robot,” ACM International Conference Proceedings, 2024.
8. ACM Digital Library Sensor Based Autonomous Color Line Follower Robot with Obstacle Avoidance, International Conference Publication, 2015.
9. Research Gate Arduino Based Hurdle Avoiding Robot, Inpressco Journal, 2025. inpressco.com
10. Line Follower and Obstacle Avoider Robot, IARJSET, 2021. IARJSET
11. Design and Construction of Line Following Robot using Arduino, ResearchGate / Conference Paper, 2020.
12. Line Follower Robot & Obstacle Detection Using PID Controller, AIP Conference Proceedings, 2020. ResearchGate
13. T. Bachim, “Line Following and Obstacle Avoidance Robot,” International Journal of Engineering Research (IJER), 2025. ijerjournal.com
14. Vicky Barua, Md. Arif Istiek Nelay, Shahid Uddin Rahat, “An Ultrasonic Line Follower Robot to Detect Obstacles and Edges,” International Journal of Computer Applications (IJCA), Vol. 176, No. 31, 2020. ijcaonline.org
15. Sai Chaya Mounika et al., “Obstacle Avoidance and Line Following 2WD Robot,” Bachelor Thesis, Blekinge Institute of Technology, 202