International Journal of Scientific Research & Engineering Trends
Volume 12, Issue 6, Nov-Dec-2026, ISSN (Online): 2395-566X

An Internet of Things Based Smart Waste Management System Using Lora and Tensorflow Deep Learning Model

Phadtate Nikita Sadashiv
Sahyadri Valley College of Engineering and Technology Savitribai Phule Pune University (SPPU), Maharashtra, India

Abstract — Rapid urbanization and increasing population have resulted in a significant rise in municipal solid waste. Conventional waste collection systems often depend on fixed schedules and manual inspection, which can lead to unnecessary collection trips, overflowing bins, increased operating costs and poor environmental conditions. This paper presents a conceptual Internet of Things (IoT) based smart waste management system that combines Long Range (LoRa) wireless communication with a TensorFlow-based deep learning model. Sensors installed in waste bins monitor parameters such as fill level and, where suitable sensors are provided, temperature or gas-related conditions. A microcontroller collects the sensor readings and transmits compact data packets through a LoRa node to a gateway. The gateway forwards the information to an application or server for storage, visualization and analysis. A TensorFlow model can classify bin status or estimate whether a bin is approaching its collection threshold using historical sensor data. The proposed approach aims to support timely collection, reduce manual monitoring and improve route planning. The paper describes the system architecture, hardware and software requirements, data flow, model development process, benefits and implementation challenges. The design is a proposed framework; actual performance must be validated through field deployment and measured data.

Keywords— Internet of Things, Smart Waste Management, LoRa, TensorFlow, Deep Learning, Sensor Networks, Waste Monitoring.

I. INTRODUCTION

Waste management is an essential public service that affects public health, cleanliness and environmental sustainability. In many cities and towns, waste bins are inspected manually or emptied according to predefined schedules. These methods do not always reflect the actual amount of waste inside each bin. A bin may become full before the scheduled collection time, while another may be collected when it is only partly filled. Such conditions can increase fuel consumption, labour requirements and the possibility of waste overflow.

The Internet of Things provides a way to connect physical devices, sensors and software platforms so that information can be collected and shared automatically. In a smart waste management system, sensors placed in bins measure their condition and send readings to a central platform. Long Range (LoRa) communication is useful for this application because it is designed for low-power, long-distance data transmission. Since sensor readings are usually small in size and do not need continuous high-bandwidth communication, LoRa can be considered for distributed waste bins.

Deep learning can add an intelligent analysis layer to the monitoring system. TensorFlow provides tools for preparing data, training models and deploying machine learning solutions. By using historical sensor readings, a model may identify patterns in bin filling behaviour, classify bin conditions or estimate when collection will be required. The combination of IoT, LoRa and TensorFlow can therefore support a more responsive waste collection process.

II. PROBLEM STATEMENT

Traditional waste collection processes may face delayed bin inspection, overflowing containers, inefficient collection routes and limited availability of real-time information. Manual monitoring of a large number of bins requires time and human effort. Fixed collection schedules may also result in unnecessary trips to bins that are not yet full. A system is therefore required to monitor bin conditions remotely, communicate the readings over a suitable low-power network and analyse the collected data to support collection decisions.

The proposed work addresses this problem by designing an IoT-based smart waste management framework using LoRa communication and a TensorFlow deep learning model. The system is intended to provide timely information about bin status and assist authorities in prioritizing collection. The model output is decision support and should be checked against

© 2026 IJSRET

real-world operating conditions before being used for automated decisions.

Objectives

- To design an IoT-based system for monitoring waste-bin conditions.
- To collect bin fill-level readings using suitable sensors.
- To transmit sensor information over a low-power, long-range LoRa link.
- To store and display bin information through a gateway and monitoring platform.
- To apply a TensorFlow deep learning model to classify bin status or estimate collection priority.
- To support efficient collection planning and reduce unnecessary manual inspection.

III. LITERATURE REVIEW

Research on smart waste management commonly explores sensor-based bin monitoring, wireless communication and centralized dashboards.

Ultrasonic sensors are frequently used to estimate the distance between the sensor and the waste surface, from which a fill-level percentage can be calculated. Other sensing options may include load cells for weight measurement and environmental sensors for detecting selected conditions. Sensor choice depends on bin shape, waste type, installation cost and maintenance requirements.

Low-power wide-area networking technologies are relevant to smart-city applications because they can connect devices that send small amounts of data over long distances. LoRa is the physical-layer radio technology, while LoRaWAN defines a network protocol and system architecture for managing communication between end devices and network servers [1], [2]. The actual coverage depends on antenna placement, obstacles, radio settings and local regulations.

TensorFlow and TensorFlow Lite provide software tools for machine learning development and deployment. Deep learning models can learn patterns from time-series sensor data, but their accuracy depends on the quality, quantity and representativeness of the training data [3], [4]. For a practical waste-management application, model performance should be compared with simple threshold-based methods to establish whether deep learning provides a meaningful improvement.

IV. PROPOSED SYSTEM

The proposed system consists of five main parts: (1) sensor unit installed in the waste bin, (2) microcontroller for reading and processing sensor values, (3) LoRa communication module, (4) LoRa gateway and server, and (5) TensorFlow-based analysis and user dashboard. Each bin is assigned a unique identification number so that readings can be associated with the correct location.

The sensor unit measures the distance from the top of the bin to the waste surface. The microcontroller converts this measurement into a fill-level value using the known internal height of the bin. The value is packaged with the bin ID, timestamp and battery or device status, if available. The LoRa module transmits this packet to a gateway. The gateway transfers the received information to a server through an available backhaul connection such as Ethernet, Wi-Fi or cellular connectivity.

At the server, readings are stored and checked for missing or abnormal values. The TensorFlow model processes suitable historical and current features to predict a bin condition or collection priority. The dashboard displays the bin location, latest fill level, last update time and model output. Collection staff can use this information to prioritize bins that require attention.

V. SYSTEM ARCHITECTURE

The overall data flow can be represented as: Waste Bin Sensors → Microcontroller → LoRa Transmitter → LoRa Gateway → Server/Database → TensorFlow Model → Monitoring Dashboard. The sensor-to-gateway link uses LoRa radio communication. The gateway-to-server link may use an Internet connection. The architecture separates local sensing from centralized analysis, allowing multiple bins to report to a shared platform.

The sensor node should be designed for low power consumption because bins may be installed at locations without convenient access to mains electricity.

Readings can be taken at selected intervals rather than continuously, depending on the required response time. The gateway should be placed where it can receive messages from the deployed nodes and connect reliably to the server.

© 2026 IJSRET

VI. HARDWARE REQUIREMENTS

A typical prototype may use an ultrasonic distance sensor to measure the distance between the sensor and the waste surface. A microcontroller board such as an ESP32 or another compatible controller reads the sensor and prepares the data packet. A LoRa transceiver module, selected for the permitted frequency band and regional radio requirements, provides long-range communication. A power supply or rechargeable battery supports the node. A gateway contains a compatible LoRa concentrator or receiver and a network connection to forward data.

Optional sensors may be added only when the application requires them. A load cell can measure the weight of waste, while temperature or gas sensors can provide selected environmental indications. These sensors do not directly identify every type of waste and require calibration. The enclosure should protect electronic components from moisture, dust, accidental impact and interference caused by waste handling.

VII. SOFTWARE REQUIREMENTS

The software layer includes microcontroller firmware, gateway forwarding software, a server-side data service, a database, a TensorFlow development environment and a dashboard. Firmware reads the sensors, validates measurements and sends a compact packet. The server receives and stores messages, checks timestamps and device identifiers, and prepares data for model inference.

TensorFlow can be used to train a classification or forecasting model. If inference is required directly on a resource-constrained microcontroller, TensorFlow Lite for Microcontrollers may be evaluated, subject to available memory and processing capacity [4]. If the model is executed on the server, the sensor node remains simpler and sends only measurements. The deployment choice should be based on latency, connectivity, power, cost and privacy requirements.

Lora Communication

LoRa is a low-power radio modulation technology intended for long-range communication. In a waste monitoring network, each sensor node can send a small data packet to a gateway. This is suitable for periodic values such as fill level, device health and battery status. LoRaWAN can be used when a standardized network protocol, device management and security mechanisms are required [1], [2].

LoRa does not provide unlimited range or guaranteed delivery. Buildings, terrain, antenna height, interference, spreading factor, transmit power and local spectrum rules affect performance. The network should therefore be tested at the intended installation sites. Message intervals and packet sizes should be selected to balance responsiveness, battery life and network capacity.

Tensorflow Deep Learning Model

The TensorFlow component analyses sensor history to provide an estimate of bin condition. A possible model input includes recent fill-level readings, the rate of change in fill level, time of day, day of week and optional weight readings. The target label may be a bin category such as 'low', 'medium' or 'nearly full', or a prediction of whether the bin will cross a defined collection threshold within a selected time window.

A practical development process begins with data collection from representative bins. The readings are labelled, checked for sensor errors and organized into training, validation and test sets. Data from the same time sequence should be split carefully to avoid information leakage. Features are normalized where appropriate. A suitable neural network, such as a small multilayer perceptron or a time-series model, can then be trained and evaluated. The simplest model that meets the required performance should be preferred.

For classification, performance can be evaluated using accuracy, precision, recall, F1-score and a confusion matrix. For forecasting, metrics such as mean absolute error may be used. Recall is particularly important when the system must avoid missing bins that are nearly full. Model predictions should be monitored after deployment because seasonal changes, local events and changes in waste patterns may reduce accuracy.

The deep learning model should not be described as experimentally validated unless measured results are available. This paper proposes the model workflow; a real deployment must report the dataset size, sensor calibration procedure, train-test split, model configuration and measured evaluation results.

Working Methodology

- Sensing: The distance sensor measures the level of waste inside the bin at a configured interval.
- Pre-processing: The controller filters invalid readings and calculates the approximate fill percentage.
- Communication: The node transmits the bin ID, reading and timestamp through LoRa.

© 2026 IJSRET

- Gateway processing: The gateway receives the packet and forwards it to the server.
- Data storage: The server validates and stores readings for monitoring and model training.
- Prediction: The TensorFlow model classifies the bin condition or estimates collection priority.
- Alert and planning: The dashboard highlights bins that need attention so that staff can plan collection.

Applications

The proposed framework can be adapted for public waste bins, college and university campuses, office complexes, hospitals, shopping areas, railway or bus stations and residential communities. In campuses, it can help housekeeping teams identify bins that need collection. In public spaces, it can provide municipal staff with a shared view of bin status. The system may also be extended to monitor selected waste storage conditions when suitable sensors and safety procedures are included.

Advantages

- Remote monitoring reduces the need for frequent manual inspection.
- LoRa supports communication over relatively long distances with low-power end devices.
- The dashboard can provide a common view of bin status and recent readings.
- Prediction of collection priority may help organize collection schedules.
- Historical data can help authorities understand waste generation patterns.
- The modular design allows additional sensors and bins to be added when network capacity permits.

Challenges and Limitations

Sensor readings can become inaccurate because of irregular waste surfaces, sensor obstruction, moisture, dust or incorrect installation. Each bin design may require calibration. LoRa coverage can be affected by buildings and local terrain, and a gateway outage can interrupt reporting. Battery replacement and device maintenance must be included in the operating plan. Deep learning requires sufficient labelled data, and an inaccurate model may produce unnecessary collection alerts or fail to identify a bin that needs service.

Security is also important. Device identity, authenticated communication, access control, secure server storage and software updates should be considered. LoRaWAN provides security features, but they must be configured and managed correctly. The system should collect only the information needed for waste operations and protect location and operational records from unauthorized access.

Future Scope

Future work may include field testing with multiple bins, comparison of LoRa and other communication technologies, and evaluation of different sensor combinations. The model may be improved using longer time-series data and local waste collection patterns. A route optimization module could combine bin priority with vehicle capacity and road-network information. Solar-assisted power, predictive maintenance and a mobile application may also be explored. Any extension should be evaluated for cost, reliability, energy use and maintainability.

VIII. CONCLUSION

This paper presents a proposed IoT-based smart waste management system using LoRa communication and a TensorFlow deep learning model. Sensors collect waste-bin readings, a microcontroller prepares the data, and LoRa transfers the information to a gateway and server. TensorFlow can analyse historical readings to classify bin status or estimate collection priority, while a dashboard provides information to waste management staff. The approach has the potential to reduce manual monitoring and support more efficient collection planning. However, its practical effectiveness depends on sensor accuracy, network coverage, reliable data collection and model validation. A prototype and field evaluation are necessary before making claims about measured performance or operational savings.

REFERENCES

1. LoRa Alliance, LoRaWAN® L2 1.0.4 Specification, 2020.
2. LoRa Alliance, LoRaWAN® Regional Parameters, RP002-1.0.4, 2023.
3. M. Abadi et al., “TensorFlow: A System for Large-Scale Machine Learning,” in Proc. 12th USENIX Symposium on Operating Systems Design and Implementation (OSDI), 2016, pp. 265–283.
4. A. Warden and D. Situnayake, TinyML: Machine Learning with TensorFlow Lite on Arduino and Ultra-Low-Power Microcontrollers. O’Reilly Media, 2019.
5. M. A. Hannan, M. Arebey, R. A. Begum, and H. Basri, “Radio Frequency Identification (RFID) and communication technologies for solid waste bin and truck monitoring system,” Waste Management, vol. 31, no. 12, pp. 2406–2413, 2011.

© 2026 IJSRET

6. M. F. U. Butt, A. A. Khan, and M. A. Qureshi, “Internet of Things (IoT) based smart waste management system: A review,” relevant research literature should be selected and verified against the final implementation before submission.
7. IEEE, IEEE Standard for Low-Rate Wireless Networks, IEEE Std 802.15.4-2020, 2020.
8. TensorFlow, “TensorFlow Lite for Microcontrollers,” TensorFlow documentation. Available: https://www.tensorflow.org/lite/microcontrollers

© 2026 IJSRET