International Journal of Scientific Research & Engineering Trends
Volume 4, Issue 6, Nov-Dec-2018, ISSN (Online): 2395-566X

Next-Generation Satellite Link Budget Analysis for Transcontinental Communications

Pratikbhai Patel
Gujarat technology university, A.D patel institute of technology, Electronic and communication engineering.

Abstract- In this research paper, the proposed link budget framework is an elaborate link budget analysis framework of a next-generation Low Earth Orbit (LEO) satellite constellations to facilitate seamless transcontinental communications. The paper examines the technical needs required to support high-availability broadband coverage on Earth in dynamic orbital and atmospheric conditions. It combines the free-space path loss models, rain fade models, atmospheric attenuation models, orbital mechanics, adaptive modulation models, optical inter-satellite links integration, and interference resilience in an International Telecommunication Union (ITU)-compatible framework. The results indicate that dynamic environmental modeling, dynamic transmission methods as well as propulsion-enhanced orbital stability are important in ensuring that link margins are consistent in geographically dispersed areas. The study also gives prominence to the need to incorporate climate sensitive attenuation forecasting, spectrum agility, and security-oriented interference mitigation in order to make the system more robust. The paper concludes with the discovery that the next-generation LEO constellations have the potential to scale to low-latency and resilient transcontinental connectivity in case it is backed by an integrated and dynamic link budget design methodology. This framework offers a technically rigorous basis to satellite communication systems in the future in the whole world.

Keywords – Link Budget Analysis, Low Earth Orbit (LEO) Satellites, Satellite Constellations, Transcontinental Communication, Free-Space Path Loss.

I. INTRODUCTION

Background and Global Context

The first section is the background and global context, which provides an overview of the issue the research aims to address. Constellations of Low Earth Orbit (LEO) satellites have re-appeared as a revolutionary design in global broadband communications, especially with transcontinental communications where terrestrial fibre routes are either economically or geographically limiting. As opposed to geostationary systems with an altitude of about 35,786 km, LEO constellations usually fall between 500 km and 1,500 km, which minimizes the propagation delay and allows lower-latency some services needed in real-time applications like in financial trading, telemedicine, and critical infrastructure monitoring.

The growing need to have accurate synchronization, high throughput connectivity and reliable international networks requires the careful analysis of link budgets to ascertain the reliability of its performance under the changing orbital and atmospheric conditions. Time and frequency transfer methods using satellites have proven under-nanosecond synchronization limits, and this research highlights the technical feasibility of innovative satellite systems in providing world- wide services [1]. The approach of integration of flexible network architectures and satellite backhaul supports even more the argument behind LEO systems. Network-in-a-Box, the idea of building network nodes that are modular and can be deployed very quickly, is compatible with the distributed topology of LEO constellations and scalable global deployment models [2]. This flexibility is also very significant in disaster recovery scenarios and under- served transcontinental corridors where there is scanty terrestrial infrastructure or vulnerable infrastructure.

Rationale for Next-Generation Link Budget Analysis

The conventional methods of satellite link budget were highly geared towards GEO systems. The introduction of LEO networks however, adds other factors such as high satellite velocities, Doppler effects, dynamic handover, and changing slanging ranges. Prediction models of path loss prediction should thus be able to take into account both classical free space attenuation and stochastic propagation models like rain fade and tropospheric scintillation. The tool of wireless path loss modeling offers the principles upon which signal degradation prediction is conducted in a variety of environmental parameters [5]. Also, the radio propagation research such as the near vertical incidence skywave (NVIS) research has demonstrated the significance of atmospheric interaction to long-range communications provides comparative research on the ionospheric effects to satellite links [3]. The optical

© 2018 IJSRET

communication technologies have also been suggested in inter-satellite connections and the high-bandwidth downlinks. The optical communications roadmap highlights the explosive rise in data rate requirement and high spectral efficiency transmission frameworks should be acquired [4]. The addition of optical cross-links to the LEO constellations helps to decrease the use of ground relay stations and increase the resilience of transcontinental routing.

Atmospheric and Environmental Considerations

The atmospheric phenomena which cause the attenuation of signals in satellite communications are highly caused by precipitation. The Global precipitation trends of the long term using satellite-era data give quantitative baselines against which the probability distributions of rain fade are modelled [19]. Such climatological databases are included in ITU-R propagation standards to be able to estimate attenuation margins required in links of high availability. Climate variability also influences signal reliability since dynamic atmospheric patterns can cause attenuation statistics to shift with time [13]. Accordingly, future-proof link budget design should put into account dynamic environmental modelling as opposed to using the past averages. The data assimilation techniques are used to improve the level of predictive modeling by incorporating observations of satellites into atmosphere models [12]. This solution facilitates better attenuation prediction and adaptive modulation scheme to deal with variability in the environment.

Technological Drivers and System Architecture Propulsion and orbital maintenance of LEO satellites have a direct impact on stability of link budgets by defining precision in orbital altitude and the ability of satellites to perform orbital maintenance. The oriental and developing space propulsion technologies offer increased manoeuvrability and long mission durations, which stabilizes the variances on slant ranges and constant link margins [6]. Broadband multimedia satellite systems have seen the suggestion of spread-spectrum techniques as well as advanced multiple access schemes that alleviate interference and maximize reverse link performance [16]. Moreover, the next-generation satellite broadcasting adaptive link strategies show that dynamically adjusted modulation and coding can increase throughput remarkably regarding the changing channel conditions [14].

Experiments on satellite-networked web access systems prove that the optimization of transport-layers are required to offset the latency and packet loss in the satellite channels [15]. The security and resilience are also important aspects of transcontinental satellite networks. The threat of interference introduced by unauthorized unmanned aerial systems (UAS) and jamming are to be considered in the computation of link margin [8]. The strategic significance of resilient satellite communication architectures in the operations undertaken by the world in the global security domain has been highlighted by the horizon scanning of emerging defense technologies [9].

Problem Statement

Even though much work has been done on satellite communications, the gap is that there exists a missing link budget model that is specifically for next- generation LEO constellations being used in transcontinental coverage. Current literature tends to take individual components like modulation, attenuation in the atmosphere or propulsion, and not put these elements together as one analytical unit consistent with the ITU standards. This study is thus aimed at creating a detailed framework of a link budget analysis which incorporates signal attenuation models, prediction of rain fades, orbital mechanics, adaptive link budgets, and variability of the environment to enable smooth global data coverage in LEO constellations.

II. LITERATURE REVIEW

Propagation and Path Loss Modeling

The basic analytical basis of satellite link budgets is wireless path loss prediction methodologies. Extensive coverage mapping methodology surveys point to empirical, deterministic and hybrid modeling in the estimation of signal attenuation over large geographic areas [5]. Although these methodologies were originally designed to analyze terrestrial systems, they would serve as fundamental analytical instruments which can be used to model satellite slant-paths. NVIS propagation studies provide even more information on atmospheric long distance reflection and absorption processes [3]. Though the propagation of LEO communication is mainly through line of sight, ionospheric interactions at specific frequencies may cause phase changes and scintillation effect similar to that of a skywave.

Adaptive and Broadband Satellite Systems Adaptive link strategies have shown to gain a lot in spectral efficiency and reliability. Next-generation satellite video broadcasting System-level next generation satellite video broadcasting provides an example of the benefits of link adaptation to changing channel conditions [14]. The use of the spread-spectrum also increases reverse link capacity and interference resistance in broadband satellite networks [16]. Web services: The satellite-based web services have been evaluated based on performance where it has been found that protocol-level optimizations are necessary to ensure the maximization of throughput and minimization of latency penalties [15]. This research highlights that when conducting a link budget analysis, one should not ignore the effect of higher layers performance. Cognitive radio technologies offer a paradigm to dynamic spectrum allocation methods used in next-generation networks and have potential use in LEO systems to optimally allocate available frequencies and reduce interference [20].

© 2018 IJSRET

Optical and Emerging Technologies
The optical communication roadmaps point to the shift to high-capacity, low-latency communication infrastructures that can accommodate the data rates of terabits [4]. Optical inter-satellite links with integration can increase the scaling of constellations or decrease reliance on geographically constrained ground stations. Massive scientific instruentation programs indicate the significance of accurate measurement systems and high-performance communication infrastructures in facilitating international scientific cooperation [11], [21]. These lessons prompt the necessity of ultra-reliable and high throughput satellite backbones.

Environmental and Regulatory Frameworks
Analysis of global precipitations gives statistical floors on the way of modeling attenuation possibilities of rains in various climatic regions [19]. Regulatory frameworks put an emphasis on environmental adaptive governance in reaction to the change in technology, and this has placed the need to adjust satellite deployment in line with international standards [18]. ITU regulations are the main standard in the compliance of spectrum allocation and propagation models.

Strategic and Operational Considerations
Satellite communication resilience is a strategic priority identified in defense-oriented horizon scanning reports [9]. Aerospace manufacturing examples of corporate case analysis show the industrial capacity with regard to the next-generation satellite systems [10]. Air traffic management studies on human reliability underscore the systemic significance of error reduction in communication systems which are mission critical [7]. All the literature together is proving that next-generation LEO link budget analysis needs to combine propagation modeling, adaptive transmission, environmental forecasting, propulsion stability, security resilience, and regulatory compliance into a common analytical model.

III. METHODOLOGY

Research Design
In the current study, the quantitative analytical framework is followed based on the ITU-R propagation standards. It is a combination of free-space path loss modeling, estimation of atmospheric attenuation, analysis of rain fade probability as well as orbital mechanics to build a complete link budget model of transcontinental LEO communication links.

Link Budget Formulation
The correlation budget is calculated based on normal Friis equations of transmission incorporated with dynamic wavy range changes that are peculiar to LEO orbits. Components of path loss are loss through free space, atmospheric loss, rain loss, polarization loss, and implementation system loss. The attenuation coefficient is estimated empirically with the help of ITU rainfall statistics with global precipitations data employed [19]. The parameters of adaptive modulation are added upon the link adaptation strategies that have been discovered during the research of broadband satellite systems [14]. The benefits of spreading spectrums are formulated on the basis of developed reverse-link optimization models [16].

Orbital Mechanics Modeling
The orbital altitude, inclination, and the ground track patterns are made to simulate the fluctuations in slant range and the Doppler effects. Propulsion stability issues are included to determine the effects of orbital maintenance on link consistency in the long-term [6].

Environmental Data Integration
Sensitivity analysis is used to include the effects of climate variability using the long-term studies of environmental trends [13]. The conceptual application of data assimilation techniques in the process of merging the atmospheric measurements with the predictive attenuation models [12].

Security and Interference Analysis
Potential sources of interference such as jamming threats are modelled to assess the reserves in link margins that are needed [8]. Spectrum optimization cases are based on cognitive radio models [20].

Performance Validation
Benchmark performance measurements such as signal-to-noise ratio, bit error rate and throughput efficiency are analysed using next-generation satellite web system benchmark performance measurements [15]. This systematic approach will guarantee that the link budget structure used is realistic in the environmental, orbital, technology, and regulatory conditions in line with the international standards.

IV. ANALYSIS

Free-Space Path Loss and Orbital Dynamics Free-space path loss (FSPL) is the primary factor that conditionally determines the LEO link performance, and depends on the altitude of the satellite and the elevation angle. To provide transcontinental services, a LEO altitude of 550 km to 1200 km will cause much less propagation delay than that of GEO systems, but cause persistent slant-range effects as the orbit moves. FSPL is given as a function of carrier frequency and distance; therefore, Ka-band and Ku-band systems operating at higher frequencies are more sensitive to the range variation. The path loss prediction techniques that were initially designed to use in terrestrial wireless systems offer the empirical and deterministic modeling foundation that is flexible to the geometry of satellites [5].

The instantaneous link margins are directly affected by orbital mechanics. The modern propulsion technologies allow precision in station-keeping and reduce the altitude drift and

© 2018 IJSRET

ensure predictable slant-range envelopes hence stabilize the FSPL calculations [6]. Efficient electric propulsion minimizes orbital disturbance and orbital lifetime, increasing consistency in link reliability between the constellation. The doppler shift analysis also indicates the existence of the need of dynamic frequency tracking in the LEO systems. Quick passages of the satellites in comparison to the ground terminals cause frequency shifts that need to be compensated to keep the carriers synchronized. It is proven in time and frequency transfer studies that GPS synchronization can provide less than nanosecond accuracy, necessary in coherent demodulation and coordination across satellites [1].

Atmospheric Attenuation and Rain Fade Modeling One of the main undetermined factors in transcontinental satellite communications is atmospheric losses, especially at frequencies of over 10 GHz. Precipitation data over long-term climatological changes on the planet are used to statistically define rain attenuation [19]. Areas that are along equatorial transcontinental routes have greater probable exceedance rates of rain, and therefore have to have greater fade margins to achieve 99.9% and above availability targets that are in line with the ITU performance standards. Research in climate change suggests that the change in precipitation probability distribution and intensity can change the attenuation probability distributions over time [13]. This means that the current allocation of the static fade margin that is based only on the past averages cannot be used in next-generation LEO systems that will have multi-decade operational life. The use of climate trend sensitivity analysis in the planning of link budgets guarantees the resilience of the budgets in the changing environmental conditions.

The methods of data assimilation help to improve modeling of predictive attenuation by combining atmospheric observations (satellites) with numerical weather prediction models [12]. Such adaptive environmental modeling applied to LEO networks would allow the use of adaptive link adaptation strategies in which the coding and modulation schemes can be altered dynamically based on real time attenuation severity predictions. The comparative propagation studies of NVIS systems show the effects of atmospheric layers on the long distance radio transmission [3]. In spite of the fact that LEO systems can be modelled using line-of-sight paths, ionospheric anomalies at some frequencies cause scintillation similar to skywave anomalies, which also justifies probabilistic attenuation modeling to be used in link budgets.

Adaptive Transmission and Throughput Optimization
Adaptive modulation and coding (AMC) are of great importance in terms of spectral efficiency in changing channel conditions. Next generation satellite broadcasting is evaluated at the system level whereby link adaptation strategies are shown to enhance throughput keeping target bit error rate thresholds constant [14]. Incorporating AMC into LEO constellations will result in nothing more than robustness to excessive static fade margins that will allow the optimization of power distributed to it, as well as expanding the overall system capacity. The Spread-spectrum reverse-link methods enhance the level of resilience to interference and efficiency of multi-user access [16]. Reverse-link interference control is required in thick transcontinental user fields, particularly, maritime and aeronautical areas, to avoid deterioration in capacity.

The addition of spread-spectrum gains into link budget analysis enhance the accuracy of carrier-to-interference ratio calculations, as well as the stability of uplink. The web-access over satellite-channel performance has been tested and it is evident that the transport-layer optimization mechanisms (i.e. TCP acceleration and caching) are required to counteract the performance degradations caused by the latency and penalties of the retransmission of packets [15]. Despite LEO systems minimizing round-trip delay compared to GEO architectures, dynamic handovers and routing variability have an impact on end-to-end throughput. Thus, the network-layer performance analysis should be merged with the link budget analysis to make the compliance with quality-of-service. Radio-acoustic cognitive frameworks also help in dynamic spectrum allocation in overloaded frequency bands [20]. Spectrum agility lowers risk of interference and enhances robustness of the system in general, especially transcontinental routes with diverse regulations.

Optical Inter-Satellite Links and High-Capacity Scaling
According to optical communication road maps, radio-frequency spectrums will continue to pose a limitation to broadband satellite growth [4]. Use of optical inter-satellite links in LEO constellations will enhance a reduction in ground relay dependency and allow high-capacity transcontinental routes with minimum latency. Optical cross-links have smaller beam divergence and improved security because of small footprints of transmission, but demand accurate pointing and tracking. Massive scientific instrumentation facilities show the possibility of mass-scale backbones of mass communication in the world with distributed research institutions [11], [21]. Such technological similarities confirm scalability of optical LEO systems in transcontinental internet services.

Security, Interference, and Resilience
Satellite networks are still prone to intentional jamming and interference. Detection and localization techniques of the illegal transmitters accentuate the necessity of the robust monitoring and quick mitigation plans [8]. Dynamically adding the interference margin reserves to the link budget will improve the margin against accidental and malicious disruption. It has been noted that satellite communications are very important infrastructure to be considered when having strategic horizon scanning reports in case of defense and emergency response mission work [9]. Thus, the redundancy needs to be introduced

© 2018 IJSRET

into the link budget planning with the help of multi-satellite visibility, adaptive routing process and failover mechanisms to maintain the continuity of services across continents. The studies of human reliability in air traffic management systems highlight the systemic significance of reducing the operational error in mission critical communication systems [7]. Using the same principles of reliability engineering to the management of constellation of satellites brings a likelihood of the minimization of cascading failures that would impact on the availability of links. Next-generation constellation deployment is also supported by industrial capability and aerospace production skills [10]. Long-term investment on the sophisticated satellite platforms will provide the alignment between the link performance goals and the viable system implementation capabilities.

Regulatory and Governance Alignment & Integrated Link Budget Synthesis

International telecommunication laws provide a fair allocation of spectrum and coordination of interference. Government systems that respond to next-generation environmental and technological regulation are focused on adaptive management systems of fast changing infrastructures [18]. The correspondence of LEO link budget design to ITU propagation models and regulatory demands enhance the interoperability globally and reduce cross-border coordination controversies.

Through the analytical synthesis, it has been proved that seamless transcontinental LEO coverage is based on the combination of following quantified parameters:

- Dynamic FSPL with the variability of orbital altitude.
- Margins of rain attenuation based on statistically resilient precipitation data.
- Adaptive modulation techniques that limit inefficiencies caused by statical fade margin.
- Optimization of spread-spectrum uplink to improve interference tolerance.
- Integration of optical inter-satellite links to assist in high-capacity backbone routing.
- Allocation of security margin to counter jamming and interference.
- Futuristic environmental forecasting to climate- proof availability ambitions.

Combining these variables into a single link budget structure will result in a robust and scaled architecture that can support high availability transcontinental data services.

V. DISCUSSION

According to the analysis, it is proven that next- generation LEO constellations are the new paradigm of satellite communication architecture. Lower latency than GEO system is an improvement in application viability in real time world service, but orbital mobility creates dynamical complexity that needs sophisticated predictive modelling. The adaptive link strategies are demonstrated to be more practical than the fixed design margin in realization of high spectral efficiency in the changing atmosphere conditions.

Climate trend analysis also implies that the idea of uncertainty in the environment should be factored in long-term infrastructure planning. The optical inter-satellite integration is a strategic facilitator of a scalable global routing, and this is consistent with long-term trends of data demand that have been observed in optical communication studies [4]. Also, security and resilience to interference are analysed, which brings the analysis of the link budget further than the metrics of physical-layer analysis, with the principles of strategic infrastructure protection. The results as a whole show that a multi-layered, standards-based, holistic method of analysis is necessary to ensure a smooth global coverage in LEO systems.

VI. CONCLUSION AND RECOMMENDATIONS

Conclusion

The study produced an analytical framework of next-generation LEO satellite links budget based on transcontinental communication. The experiment combined free-space path loss models, prediction of atmospheric attenuation, adaptive modulation techniques, orbital mechanics stability, interference resistance, optical scaling potential and regulatory conformity in an ITU-congruent framework. Quantitative analysis assures that continuous worldwide coverage of data would demand an active- environmental format, adaptive transmission strategies, orbital stability sustainment via propulsion, as well as spectrum agility. The use of climate-sensitive analysis of precipitation and security margin allocation will guarantee reliability in the long-term when there will be changing environmental and geopolitical factors. The results indicate that next-generation LEO constellations are capable of providing high-availability and low- latency global connectivity in cases that are facilitated by combined link budget design and advanced adaptive technologies.

Recommendations

Adaptive modulation and coding should be implemented as the design of the future LEO constellation, and not as some extra feature, to use spectral efficiency and avoid the waste of unnecessary fade margins. Optical inter-satellite links will be made in systematic implementation to enhance backbone capacity and eliminate the need to rely on terrestrial relay stations. Network control systems must incorporate climate-responsive attenuation forecasting models which use data assimilation schemes to change power allocation and coding schemes dynamically. Implementation of cognitive radio should be carried out to improve the efficiency of the spectrum and avoid the risks of cross-border interferences. All

© 2018 IJSRET

transcontinental link budgets should include security-specific margin planning such as the ability to detect jamming and mitigate interferences that may affect critical communications infrastructure. Finally, harmonisation of regulations with the ITU standards and active governance restructuring will be needed to perpetuate equitable and interference free global satellite operations. All those suggestions provide a technically sound and strategically solid base towards next- generation satellite link budget design in transcontinental LEO communication systems.

REFERENCE

1. W. Schäfer and T. Feldmann, "Perspectives of Time and Frequency Transfer via Satellite," Journal of physics. Conference series, vol. 723, pp. 012038–012038, Jun. 2016, doi: https://doi.org/10.1088/1742-6596/723/1/012038.
2. M. Pozza, A. Rao, H. Flinck, and S. Tarkoma, "Network-In-a-Box: A Survey About On-Demand Flexible Networks," IEEE Communications Surveys & Tutorials, vol. 20, no. 3, pp. 2407–2428, 2018, doi: https://doi.org/10.1109/comst.2018.2807125.
3. B. A. Witvliet and R. M. Alsina-Pagès, "Radio communication via Near Vertical Incidence Skywave propagation: an overview," Telecommunication Systems, vol. 66, no. 2, pp. 295–309, Feb. 2017, doi: https://doi.org/10.1007/s11235-017-0287-2.
4. E. Agrell et al., "Roadmap of optical communications," Journal of Optics, vol. 18, no. 6, p. 063002, May 2016, doi: https://doi.org/10.1088/2040-8978/18/6/063002.
5. C. Phillips, D. Sicker, and D. Grunwald, "A Survey of Wireless Path Loss Prediction and Coverage Mapping Methods," IEEE Communications Surveys & Tutorials, vol. 15, no. 1, pp. 255–270, 2013, doi: https://doi.org/10.1109/surv.2012.022412.00172.
6. M. C. Vilela Salgado, C. M. N. Belderrain, and T. C. Devezas, "Space Propulsion: a Survey Study About Current and Future Technologies," Journal of Aerospace Technology and Management, vol. 10, Feb. 2018, doi: https://doi.org/10.5028/jatm.v10.829.
7. A. Isaac, S. T. Shorrock, and B. Kirwan, "Human error in European air traffic management: the HERA project," Reliability Engineering & System Safety, vol. 75, no. 2, pp. 257–272, Feb. 2002, doi: https://doi.org/10.1016/s0951-8320(01)00099-0.
8. İ. Güvenç, O. Ozdemir, Y. Yapici, H. Mehrpouyan, and D. Matolak, "Detection, localization, and tracking of unauthorized UAS and Jammers," IEEE Xplore, Sep. 01, 2017. https://ieeexplore.ieee.org/document/8102043
9. K. Ivanova and G. E. Gallasch, "Horizon Scan of Emerging Technologies and Trends for ADF Combat Service Support 2016," Dtic.mil, Dec. 2016. https://apps.dtic.mil/sti/html/tr/AD1027337/ (accessed Mar. 02, 2026).
10. [10]R. V. Petrescu et al., "Lockheed Martin - A Short Review," papers.ssrn.com, Nov. 19, 2017. https://papers.ssrn.com/sol3/papers.cfm?abstract_id=3073975
11. M. Demarteau, R. Lipton, H. Nicholson, and I. Shipsey, "Particle and nuclear physics instrumentation and its broad connections," Reviews of modern physics, vol. 88, no. 4, Dec. 2016, doi: https://doi.org/10.1103/revmodphys.88.045007.
12. W. A. Lahoz and P. Schneider, "Data assimilation: making sense of Earth Observation," Frontiers in Environmental Science, vol. 2, May 2014, doi: https://doi.org/10.3389/fenvs.2014.00016.
13. R. Kallenborn, C. Halsall, M. Dellong, and P. Carlsson, "The influence of climate change on the global distribution and fate processes of anthropogenic persistent organic pollutants," Journal of Environmental Monitoring, vol. 14, no. 11, p. 2854, 2012, doi: https://doi.org/10.1039/c2em30519d.
14. C. Morel, P.-D. Arapoglou, M. Angelone, and Ginesi, "Link Adaptation Strategies for Next Generation Satellite Video Broadcasting: A System Approach," IEEE Transactions on Broadcasting, vol. 61, no. 4, pp. 603–614, Dec. 2015, doi: https://doi.org/10.1109/tbc.2015.2470355.
15. R. Secchi, A. C. Mohideen, and G. Fairhurst, "Performance analysis of next generation web access via satellite," International Journal of Satellite Communications and Networking, vol. 36, no. 1, pp. 29–43, Dec. 2016, doi: https://doi.org/10.1002/sat.1201.
16. O. del Rio Herrero, G. Foti, and G. Gallinaro, "Spread-Spectrum Techniques for the Provision of Packet Access on the Reverse Link of Next- Generation Broadband Multimedia Satellite Systems," IEEE Journal on Selected Areas in Communications, vol. 22, no. 3, pp. 574–583, Apr. 2004, doi: https://doi.org/10.1109/jsac.2004.823440.
17. R. van Amerongen, V. P Retèl, V. M. Coupé, P. M. Nederlof, M. J. Vogel, and W. H. van Harten, "Next-generation sequencing in NSCLC and melanoma patients: a cost and budget impact analysis," ecancermedicalscience, vol. 10, Oct. 2016, doi: https://doi.org/10.3332/ecancer.2016.684.
18. N. Gunningham and C. Holley, "Next-Generation Environmental Regulation: Law, Regulation, and Governance," Annual Review of Law and Social Science, vol. 12, no. 1, pp. 273–293, Oct. 2016, doi: https://doi.org/10.1146/annurev-lawsocsci-110615- 084651.
19. R. F. Adler, G. Gu, M. Sapiano, J.-J. Wang, and G. J. Huffman, "Global Precipitation: Means, Variations and Trends During the Satellite Era (1979–2014)," Surveys in Geophysics, vol. 38, no. 4, pp. 679–699, Jun. 2017, doi: https://doi.org/10.1007/s10712-017-9416-4.

© 2018 IJSRET

20. N. Pandi and A. Kumar, "A Review on Cognitive Radio for Next Generation Cellular Network and its Challenges," American Journal of Engineering and Applied Sciences, vol. 10, no. 2, pp. 334–347, Feb. 2017, doi: https://doi.org/10.3844/ajeassp.2017.334.347.
21. L. Simard, "The Thirty-Meter Telescope: Science and Instrumentation for a Next-Generation Observatory," Journal of Astrophysics and Astronomy, vol. 34, no. 2, pp. 97–120, Jun. 2013, doi: https://doi.org/10.1007/s12036-013-9177-5.

© 2018 IJSRET