International Journal of Scientific Research & Engineering Trends
Volume 12, Issue 5, Sep-Oct-2026, ISSN (Online): 2395-566X

Intelligent Energy Management in Renewable-Integrated Smart Grids: A Review of Advanced Metering, Demand Response, Energy Storage and Ai-Based Forecasting

Patil Saurabh Dnyaneshwar[1] Shelke Sanskar Ramesh[2] Sukhadeve Nitesh Suryabhan[3], Prof. M. S. Nalawade[4] Dr. V. M. Dhede[5]

[1,2,3]Department Of Electronics And Telecommunication Jaihind College Of Engineering Kuran, Pune, Maharashtra, India
[4]Seminar Guide & Seminar Coordinator Department of Electronics and Telecommunication
Jaihind College of Engineering Kuran, Pune, Maharashtra, India
[5]Head of Department Department of Electronics and Telecommunication Jaihind College of Engineering Kuran, Pune, Maharashtra, India

Abstract—A sustainable electricity system must supply growing demand with an increasing share of solar, wind and hydro generation whose output cannot be scheduled at will. Balancing such a system depends less on adjusting a few large power plants and more on managing energy intelligently across millions of consumers, storage units and distributed generators. This review focuses on the demand side and the information layer of the smart grid. It examines advanced metering infrastructure, which provides two-way communication between utilities and consumers; demand response and demand-side management, which shift or reduce consumption in response to prices or signals; energy storage and electric vehicles, which absorb surplus renewable energy and release it when needed; and forecasting of load and renewable generation using statistical and machine-learning models. Representative studies on each topic are compared. A layered architecture for an intelligent energy management system is presented in which consumer devices, smart meters, communication networks, an energy management platform and utility services cooperate to minimise cost, losses and emissions while maintaining reliability. Communication requirements, cyber security, privacy and consumer participation are discussed as challenges, and directions such as reinforcement-learning-based demand response and local energy markets are identified.

Index Terms—Smart grid, renewable energy, energy management system, advanced metering infrastructure, demand response, energy storage, load forecasting, machine learning, vehicle-to-grid, cyber security.

I. INTRODUCTION

Electricity demand is growing with urbanisation, air conditioning, digital services and the electrification of transport. At the same time, power systems are adding large amounts of solar, wind and hydro generation to reduce pollution and dependence on fossil fuels. Renewable sources lower emissions but are variable: solar output disappears in the evening just as household demand peaks, and wind output may change significantly within hours. Keeping supply and demand in balance therefore becomes more difficult.

Traditionally, balance was maintained by adjusting the output of dispatchable power plants to follow demand. In a grid with high renewable share, it is more economical and cleaner to make demand, storage and distributed resources flexible as well. This requires the smart grid's information and control capabilities. Farhangi described the smart grid as an evolution towards a system with intelligence and communication at every level, from generation to the consumer's premises [1]. Palensky and Dietrich explained that demand-side management, including demand response and intelligent loads, is a central part of this vision [2].

This paper reviews intelligent energy management in renewable-integrated smart grids. Its contributions are:

- A review of advanced metering infrastructure and smart-grid communication.
- A review of demand response, demand-side management and their optimisation.
- A review of energy storage and electric vehicles as flexible resources.
- A review of load and renewable forecasting methods, including machine learning.
- A layered architecture for an intelligent energy management system, and a discussion of challenges.

Section II gives the background, Section III reviews advanced metering, Section IV reviews demand response,

© 2026 IJSRET

Section V covers storage and electric vehicles, Section VI covers forecasting, Section VII presents the architecture, Section VIII compares approaches, Section IX discusses challenges, and Section X concludes.

II. BACKGROUND

2.1 The Balancing Problem

At every moment, generation must equal consumption plus losses. With renewables, it is useful to define the *net load* that conventional plants and flexible resources must cover:

$$L_{net}(t) = L(t) - P_{PV}(t) - P_{wind}(t) \qquad (1)$$

A large midday solar output can make net load very low, while the evening fall in solar output produces a steep ramp. Managing these variations at low cost is the central task of energy management.

2.2 Energy Management Systems

An energy management system (EMS) collects measurements, forecasts demand and generation, and schedules resources to minimise operating cost subject to technical limits. In a microgrid or building, the EMS may control batteries, flexible loads and local generation [3]. At utility scale, it coordinates demand response programmes and storage with conventional generation.




Fig. 1. Classification of intelligent energy management techniques for smart grids.

III. ADVANCED METERING INFRASTRUCTURE

Advanced metering infrastructure (AMI) consists of smart meters at consumer premises, communication networks, data concentrators and a meter data management system at the utility. Mohassel *et al.* surveyed AMI and described its functions, including interval measurement of consumption, remote reading and connection, outage detection and support for time-varying tariffs [4]. AMI provides the data and two-way communication that demand response and forecasting require.

Smart-grid communication is often described by its coverage: home area networks (HAN) connect appliances to the meter, neighbourhood area networks (NAN) connect meters to concentrators, and wide area networks (WAN) connect concentrators to utility control centres. Gungor *et al.* and Yan *et al.* reviewed the technologies for these networks, including ZigBee, Wi-Fi, power line communication, cellular and fibre, and their requirements for latency, reliability and security [5], [6].

IV. DEMAND RESPONSE AND DEMAND-SIDE MANAGEMENT

4.1 Programme Types

Albadi and El-Saadany classified demand response (DR) into incentive-based programmes, such as direct load control, interruptible service and demand bidding, and price-based programmes, such as time-of-use, critical-peak and real-time pricing [7]. Under price-based DR, consumers shift flexible consumption to cheaper periods, which often coincide with high renewable output.

4.2 Optimisation Of Consumption

Mohsenian-Rad *et al.* proposed an autonomous demand-side management scheme in which smart meters schedule household appliances using a game-theoretic approach, reducing peak-to-average ratio and total energy cost for all participants [8]. In general, a home EMS schedules flexible appliances to minimise cost over a horizon of T intervals:

$$\min \Sigma_{t=1}^{T} p(t) \cdot [L(t) - P_{PV}(t) + P_B(t)] \qquad (2)$$

where $p(t)$ is the price, $L(t)$ the household load, $P_{PV}(t)$ local solar generation and $P_B(t)$ battery charging power (negative when discharging), subject to appliance deadlines and battery limits.

4.3 Dr As A Market Resource

Rahimi and Ipakchi described how demand response can participate in electricity markets alongside generation, providing capacity, energy and ancillary services when aggregated across many consumers [9].

4.4 Learning-Based Demand Response

Vázquez-Canteli and Nagy reviewed reinforcement learning (RL) for demand response, in which a controller learns to operate heating, cooling, storage or appliances by trial and reward without a detailed model of the building [10]. RL

© 2026 IJSRET

can adapt to individual consumer behaviour and changing prices.

4.5 Energy Storage And Electric Vehicles
4.6 Storage Technologies

Luo *et al.* reviewed electrical energy storage technologies and their application in power system operation, including pumped hydro, compressed air, batteries, flywheels and supercapacitors [11]. Lithium-ion batteries dominate new installations because of their high efficiency, fast response and modularity. Storage can shift surplus solar energy to evening peaks, reduce renewable curtailment, provide frequency regulation and defer network upgrades.

4.7 Electric Vehicles And Vehicle-To-Grid

Electric vehicles represent a large and growing flexible load. Smart charging shifts charging to periods of low demand or high renewable output. With bidirectional chargers, vehicles can also return energy to the grid. Kempton and Tomić analysed vehicle-to-grid (V2G) power and showed that aggregated EV batteries could provide regulation services and support large-scale renewable integration [12].

V. FORECASTING OF LOAD AND RENEWABLE GENERATION

5.1 Load Forecasting

Hong and Fan reviewed probabilistic load forecasting and argued that forecasts should express uncertainty, through quantiles or intervals, because operating decisions depend on risk as well as on expected values [13]. Kong *et al.* applied long short-term memory (LSTM) recurrent neural networks to short-term residential load forecasting using smart-meter data and found them more accurate than several conventional methods for individual households [14].

5.2 Renewable Forecasting

Larson, Nonnenmacher and Coimbra developed day-ahead forecasts of PV plant output using numerical weather prediction data, demonstrating useful accuracy for scheduling [15]. Forecasts of renewable generation allow the EMS to plan storage and demand response in advance rather than reacting after the fact.

Table I Summary Of Representative Studies On Smart-Grid Energy Management

Ref.	Area	Contribution	Key Finding	Limitation
[4]	AMI	Survey of advanced metering infrastructure	Defines AMI components and functions	Limited security depth
[7]	Demand response	Classification of DR programmes	Price-based and incentive-based DR	Market-focused summary
[8]	DSM	Game-theoretic appliance scheduling	Lower peak-to-average ratio and cost	Assumes rational, informed users
[10]	Learning DR	Review of RL for demand response	Model-free adaptive control	Training time, safety
[14]	Load forecasting	LSTM for residential load	Higher accuracy for households	Data and computation needs
[15]	PV forecasting	Day-ahead PV forecasts from weather data	Useful day-ahead accuracy	Regional climate dependence
[12]	V2G	Vehicle-to-grid implementation analysis	EVs can provide grid services	Battery wear, infrastructure

VI. INTELLIGENT ENERGY MANAGEMENT ARCHITECTURE




Fig. 2 presents a layered architecture for intelligent energy management in a renewable-integrated smart grid.

© 2026 IJSRET

The **consumer layer** includes homes, buildings and industries with smart appliances, rooftop solar, batteries and EV chargers. The **metering layer** consists of smart meters and home energy management units that measure consumption at short intervals and receive price or control signals [4]. The **communication layer** links HAN, NAN and WAN segments with secure protocols [5], [6]. The **energy management layer** hosts forecasting models for load and renewables [14], [15], optimisation and learning engines for demand response [8], [10], and scheduling of storage and EV charging [11], [12]. The **utility and market layer** sets tariffs, runs DR programmes, procures ancillary services and coordinates with system operators [9]. A cross-layer security and privacy function protects data and control commands [16].

The operation proceeds in a cycle. Forecasts of the next day's load and renewable generation are prepared; the EMS determines storage schedules, DR events and price signals that flatten net load and maximise renewable use; consumer devices respond automatically within user-defined comfort limits; and actual measurements are fed back to improve forecasts and settle payments.

VII. COMPARATIVE ANALYSIS

Table II compares the main sources of flexibility for renewable-integrated grids

.

Resource	Response Time	Flexibility Duration	Main Benefit	Main Limitation
Price-based DR [7]	Hours (scheduled)	Hours	Low cost, wide reach	Uncertain consumer response
Direct load control [7]	Minutes	Minutes to hours	Reliable, dispatchable	Comfort impact, consent
Automated home DSM [8]	Seconds to minutes	Hours	Peak reduction, cost saving	Requires smart appliances
Battery storage [11]	Milliseconds	Minutes to hours	Fast, bidirectional	Capital cost, ageing
EV smart charging and V2G [12]	Seconds	Hours	Uses existing batteries	Availability, battery wear
Forecast-driven scheduling [13], [14]	Planning tool	Day-ahead	Reduces reserve needs	Forecast errors

VIII. CHALLENGES AND FUTURE DIRECTIONS

Several challenges must be overcome. **Cyber security**: the two-way communication that enables energy management also creates attack surfaces; Wang and Lu reviewed threats to smart grids, including denial of service and manipulation of meter data, and the countermeasures required [16]. **Privacy**: fine-grained meter data can reveal household routines, so data minimisation, aggregation and privacy-preserving analytics are needed. **Consumer participation**: the benefits of DR depend on consumers who may not respond to price signals, which calls for automation and simple, fair incentives [2]. **Interoperability**: devices from many manufacturers must communicate through common standards [5]. **Forecast uncertainty**: renewable and load forecast errors must be handled through probabilistic forecasts and robust scheduling [13]. **Scalability**: coordinating millions of devices requires distributed and hierarchical control. Future directions include RL-based home and building energy management [10], aggregation of distributed resources into virtual power plants, local peer-to-peer energy markets, and coordinated V2G services.

IX. CONCLUSION

Integrating renewable energy at scale requires more than new generation; it requires intelligent management of energy throughout the grid. This review has shown how advanced metering infrastructure provides the data and communication, how demand response and demand-side management make consumption flexible, how storage and electric vehicles absorb and release energy, and how statistical and machine-learning forecasting allow resources to be planned in advance. The layered architecture presented here brings these elements together to reduce cost, losses and emissions while maintaining reliability. Addressing security, privacy, participation and scalability will allow intelligent energy management to support a cleaner, greener and more reliable electricity future.

REFERENCES

1. H. Farhangi, "The path of the smart grid," IEEE Power and Energy Magazine, vol. 8, no. 1, pp. 18–28, 2010.
2. P. Palensky and D. Dietrich, "Demand side management: Demand response, intelligent energy systems, and smart loads," IEEE Transactions on Industrial Informatics, vol. 7, no. 3, pp. 381–388, 2011.

© 2026 IJSRET

3. D. E. Olivares et al., "Trends in microgrid control," IEEE Transactions on Smart Grid, vol. 5, no. 4, pp. 1905–1919, 2014.
4. R. R. Mohassel, A. Fung, F. Mohammadi, and K. Raahemifar, "A survey on advanced metering infrastructure," International Journal of Electrical Power & Energy Systems, vol. 63, pp. 473–484, 2014.
5. V. C. Gungor, D. Sahin, T. Kocak, S. Ergut, C. Buccella, C. Cecati, and G. P. Hancke, "Smart grid technologies: Communication technologies and standards," IEEE Transactions on Industrial Informatics, vol. 7, no. 4, pp. 529–539, 2011.
6. Y. Yan, Y. Qian, H. Sharif, and D. Tipper, "A survey on smart grid communication infrastructures: Motivations, requirements and challenges," IEEE Communications Surveys & Tutorials, vol. 15, no. 1, pp. 5–20, 2013.
7. M. H. Albadi and E. F. El-Saadany, "A summary of demand response in electricity markets," Electric Power Systems Research, vol. 78, no. 11, pp. 1989–1996, 2008.
8. A.-H. Mohsenian-Rad, V. W. S. Wong, J. Jatskevich, R. Schober, and A. Leon-Garcia, "Autonomous demand-side management based on game-theoretic energy consumption scheduling for the future smart grid," IEEE Transactions on Smart Grid, vol. 1, no. 3, pp. 320–331, 2010.
9. F. Rahimi and A. Ipakchi, "Demand response as a market resource under the smart grid paradigm," IEEE Transactions on Smart Grid, vol. 1, no. 1, pp. 82–88, 2010.
10. J. R. Vázquez-Canteli and Z. Nagy, "Reinforcement learning for demand response: A review of algorithms and modeling techniques," Applied Energy, vol. 235, pp. 1072–1089, 2019.
11. X. Luo, J. Wang, M. Dooner, and J. Clarke, "Overview of current development in electrical energy storage technologies and the application potential in power system operation," Applied Energy, vol. 137, pp. 511–536, 2015.
12. W. Kempton and J. Tomić, "Vehicle-to-grid power implementation: From stabilizing the grid to supporting large-scale renewable energy," Journal of Power Sources, vol. 144, no. 1, pp. 280–294, 2005.
13. T. Hong and S. Fan, "Probabilistic electric load forecasting: A tutorial review," International Journal of Forecasting, vol. 32, no. 3, pp. 914–938, 2016.
14. W. Kong, Z. Y. Dong, Y. Jia, D. J. Hill, Y. Xu, and Y. Zhang, "Short-term residential load forecasting based on LSTM recurrent neural network," IEEE Transactions on Smart Grid, vol. 10, no. 1, pp. 841–851, 2019.
15. D. P. Larson, L. Nonnenmacher, and C. F. M. Coimbra, "Day-ahead forecasting of solar power output from photovoltaic plants in the American Southwest," Renewable Energy, vol. 91, pp. 11–20, 2016.
16. W. Wang and Z. Lu, "Cyber security in the smart grid: Survey and challenges," Computer Networks, vol. 57, no. 5, pp. 1344–1371, 2013.

© 2026 IJSRET